



Engineering, LLC

**PROJECT NARRATIVE
AND
STORM DRAINAGE ANALYSIS
FOR**

**ARLINGTON HEIGHTS INDUSTRIAL
703-723 ALGONQUIN ROAD
ARLINGTON HEIGHTS, IL**

PREPARED FOR:

**MORGAN/HARBOUR CONSTRUCTION LLC
7510 SOUTH MADISON STREET
WILLOWBROOK, IL 60527
630-734-7737**

PREPARED BY:

RWG Engineering, LLC

975 E. 22nd Street
Suite 400
Wheaton, Illinois 60189
(630) 480-7889

**JOB# 322-127-17-301
OCTOBER 18, 2017**

Table of Contents

- Narrative Description of Proposed Development (2 pages)
- Table 1 – Drainage Summary Sheet (1 page)
- Restrictive Culvert Worksheet-Existing Storm Outfalls (3 pages)
- Orifice Worksheet-Proposed Orifice Size for Phase 1 & 2 (2 pages)
- Arlington Heights Storage Volume Calculation Sheets With Allowable Release Rate -- Ph 1 Temporary, Ph 1 Build-Out & Ph 2 (3 pages)
- Arlington Heights Storage Volume Calculation Sheets With Design Release Rate -- Ph 1 Temporary, Ph 1 Build-Out & Ph 2 (3 pages)
- MWRD Runoff Curve Number, Adjustment Calculator & Detention Volume Vs Reduced Curve Number Sheets – Ph 1 Temp Cond, P1 Build-out & Ph 2 Build-Out (9 pages)
- Table 2 – Summary of Stormwater Storage Provided (1 page)
- Cut/Fill Report – Storage Volumes Provided (1 page)
- Detention Storage in Storm Sewer System (1 page)
- Weir Flow Calculations – Ph 1 & 2 (2 pages)
- Storm Sewer Worksheet – Ph 1 North (3 - 11x17 pages)
- Storm Sewer Worksheet – Ph 2 East & West Section (2 – 11x17 pages)
- Boundary Survey – Existing Parcel (1 - 11x17 page)
- Existing Drainage Exhibit (2 – 11x17 pages)
- Phase 1 (North) Proposed Drainage Area Exhibit (1- 11x17 page)
- Proposed Master Drainage Area Exhibit (1 – 11x17 page)

October 18, 2017

File: 322-127-17

Arlington Heights Industrial

703-723 Algonquin Road
Arlington Heights, IL
15.41 Acre Property

Narrative Description of Proposed Development

(Refer Also to Final Engineering Plans, Notes and Exhibits.)

General:

The subject parcel is located southeasterly of Algonquin Road and Meijer Drive in Arlington Heights, Illinois. The Jane Adams Memorial Tollway (I-90) is along the southern boundary of the property. Currently, two light industrial/office buildings are on the site. The northern building is on existing Parcel 1, which consists of 7.04 acres. The southern building is on existing Parcel 2, which consists of 8.37 acres. The proposed improvements include one building of approximately 331,000 sq ft for warehousing/distribution. Construction is to proceed in two phases. The first phase would be on existing Parcel 1, during which time the existing building on Parcel 2 would remain operational. With the Phase 2 improvements, the Phase 1 building would extend into the Parcel 2 area. Since the site currently consists of two parcels, a Plat of Subdivision combining the site into one lot is proposed.

Stormwater Management:

The existing Parcel 1 drains to the north with a storm drain connection at the northeast corner of the parcel to the existing 18" storm sewer along the southerly side of Algonquin Road. Storm water discharge from the site is controlled by an existing 4" PVC pipe, as well as a secondary 10" RCP pipe at a higher elevation. The existing overland flow from Parcel 1 to Algonquin Rd is within the easterly driveway at an approximate elevation of 715.43. No improvements to this existing driveway are proposed within the Algonquin Rd right-of- way. Therefore, for design purposes an overflow elevation of 715.4 is used. At the 715.4 elevation, the existing 4" PVC has a release of approximately 0.69 cfs and the 10" RCP has a release of 4.44 cfs, for a total of 5.13 cfs.

The existing Parcel 2 drains to the south, via an existing 18" RCP pipe, which connects to an existing 36" storm sewer with discharge to an open waterway along the north side of I-90. No restrictor was located within the existing 18" RCP storm sewer. The existing overland flow from parcel 2 is to the south at an approximate elevation of 715.0. At this 715.0 overflow elevation, the existing release thru the 18" RCP is approximately 21.17". Since there is no offsite area tributary to Parcel 2 which would be impacted by a slight rise in the overflow elevation, a 715.4 high water level (HWL)/overflow elevation is used for both the Phase 1 and Phase 2 site improvements.

Stormwater detention requirements were reviewed for both the Village of Arlington Heights, and the Metropolitan Water Reclamation District of Greater Chicago (MWRD) criteria. Also, the MWRD volume control requirements were reviewed. Since there are some slight deviations in the Phase 2 improvements draining to the north from the proposed site improvements with Phase 1, both conditions were reviewed. In consideration of the worst case scenario, the proposed design implements the more restrictive criteria. A Drainage Summary Sheet, Table 1, is attached which provides a summary of the allowable release rate, as well as the detention, and volume control requirements for the various scenarios.

For the north drainage area in the proposed condition, the existing 4" PVC is to remain, and a 3-1/8" orifice plate is to be provided in the existing 10" RCP. This results in a total release of 1.21 cfs at the 715.4 elevation. For the south drainage area, a 5" orifice plate is proposed for the 18" RCP, restricting the release to 1.53 cfs at the 714.4 HWL.

The detention volumes associated with the above design release rates were reviewed. Per the attached calculations, using these design release rates, the detention storage volume for the north area would be 2.69 ac-ft, and 3.16 ac-ft for the south, phase 2 area.

A Summary of Storage Provided, Table 2, is attached outlining the storage volumes provided in the respective basins and locations. Although, there may be some minor refinement of allocations between detention and volume control storage in the underground basins, the total volumes provided are appropriate based on both the Village of Arlington Heights and the MWRD criteria. As noted, stormwater storage is provided in a combination of areas, including vegetated/open water basins, underground storage, pipe storage, and surface ponding in the truck dock areas. It is noted the ponding in the truck dock areas will occur during the more intense storms only, with the proposed rims at a 714.05 elevation. Therefore, at the upper elevations of the detention storage system, a maximum water depth of 1.35' would be expected at the 715.4 HWL/overflow elevation.

TABLE 1 -- ARLINGTON HEIGHTS INDUSTRIAL - DRAINAGE SUMMARY SHEET

VILLAGE OF ARLINGTON HEIGHTS CRITERIA:

Temp. DRAINAGE AREA (Ac.)	Offsite DRAINAGE AREA (Ac.)	Temp. TOTAL AREA (Ac.)	DRAINAGE AREA (Ac.)	Offsite DRAINAGE AREA (Ac.)	TOTAL AREA (Ac.)	IMPERVIOUS AREA (Ac.) onsite only	IMPERVIOUS AREA (Ac.) Total w/ offsite	% Impervious	COMPOSITE "C"	ALLOWABLE RELEASE (cfs)	Detention Required (ac- ft)
7.04	0.396	7.436				5.843	5.902	80%	0.86	1.33	2.60
			6.875	0.396	6.934	5.957	6.016	87%	0.89	1.24	2.55
			8.540	0.016	8.556	7.498	7.514	88%	0.90	1.54	3.16

PHASE 2: full build out

PHASE 1: full build out

PHASE 1: first phase only
(temporary condition)

MMWRD CRITERIA:

Temp. DRAINAGE AREA (Ac.)	Offsite DRAINAGE AREA (Ac.)	Temp. TOTAL AREA (Ac.)	DRAINAGE AREA (Ac.)	Offsite DRAINAGE AREA (Ac.)	TOTAL AREA (Ac.)	IMPERVIOUS AREA (Ac.) onsite only	IMPERVIOUS AREA (Ac.) Total w/ offsite	% Impervious	COMPOSITE "C"	ALLOWABLE RELEASE (cfs)	Detention Required (ac- ft)
7.04	0.396	7.436				5.843	5.902	80%	93	2.23	1.75
			6.875	0.396	6.934	5.957	6.016	87%	95	2.08	1.70
			8.540	0.016	8.556	7.498	7.514	88%	95	2.57	2.09

PHASE 1: first phase only
(temporary condition)

PHASE 1: full build out

PHASE 2: full build out

MMWRD VOLUME CONTROL:

PHASE 1 (full build out-max impervious)	1" of volume over total impervious area of -----	6.016	Ac	Required Volume =	0.50	Ac-Ft
PHASE 2 (full build out)	1" of volume over total impervious area of -----	7.514	Ac	Required Volume =	0.63	Ac-Ft

RESTRICTIVE CULVERT WORKSHEET

JOB DATA:

Job Name:	ALGONQUIN RD INDUSTRIAL-PH 1
Job Number:	322-127-17
Designer:	PDL
Description	EXIST STORM OUTFALL-4" PRIMARY

FLows ARE BASED ON THE FOLLOWING EQUATION:

$$Q = A \sqrt{\frac{H}{\frac{K_e + K_o}{2g} + \frac{2.87(n)^2 L}{3\sqrt{\phi^4}}}}$$

Q = FLOW (cfs)

A = AREA (sqr.ft.)

H = Head (ft.)

K_e & K_o = Entrance & Outlet Loss Coefficients

n = Manning's Roughness Coefficient

g = 32.2 ft/sec²

= diameter

ϕ

PIPE DATA:

Pipe Diameter (feet)	0.33	ft.
Pipe Area (sqr. ft)	0.087	sqr. ft.
Slope (ft./ft.)	-0.0023	
Length of Pipe (ft.)	30	ft.
Existing Invert Elevation	709.67	ft.
Backwater Elevation	710.07	ft. (Top of 4" pipe @ outlet)
Manning's "n" value	0.013	
Entrance Loss Coefficient	0.50	
Outlet Loss Coefficient	1.00	

RATING TABLE:

Water Elevation (ft.)*	Head (ft.)	Q (cfs)
715.00	4.93	0.66
715.10	5.03	0.67
715.20	5.13	0.67
715.30	5.23	0.68
715.40	5.33	0.69
715.50	5.43	0.69
715.60	5.53	0.70
715.70	5.63	0.70
715.80	5.73	0.71
715.90	5.83	0.72
716.00	5.93	0.72

*Water elevation must be higher than backwater elevation.

RESTRICTIVE CULVERT WORKSHEET

JOB DATA:

Job Name:	ALGONQUIN RD INDUSTRIAL-PH 1
Job Number:	322-127-17
Designer:	PDL
Description	EXIST STM OUTFALL-10" SECONDARY

FLows ARE BASED ON THE FOLLOWING EQUATION:

$$Q = A \sqrt{\frac{H}{\frac{K_e + K_o}{2g} + \frac{2.87(n)^2 L}{\sqrt[3]{\phi^4}}}}$$

Q = FLOW (cfs)

A = AREA (sqr.ft.)

H = Head (ft.)

K_e & K_o = Entrance & Outlet Loss Coefficients

n = Manning's Roughness Coefficient

g = 32.2 ft/sec²

= diameter

ϕ

PIPE DATA:

Pipe Diameter (feet)	0.83	ft.
Pipe Area (sqr. ft)	0.541	sqr. ft.
Slope (ft./ft.)	-0.021	
Length of Pipe (ft.)	30	ft.
Existing Invert Elevation	711.12	ft.
Backwater Elevation	712.58	ft. (Top of 10" pipe @ outlet)
Manning's "n" value	0.013	
Entrance Loss Coefficient	0.50	
Outlet Loss Coefficient	1.00	

RATING TABLE:

Water Elevation (ft.)*	Head (ft.)	Q (cfs)
715.00	2.42	4.11
715.10	2.52	4.19
715.20	2.62	4.28
715.30	2.72	4.36
715.40	2.82	4.44
715.50	2.92	4.51
715.60	3.02	4.59
715.70	3.12	4.67
715.80	3.22	4.74
715.90	3.32	4.81
716.00	3.42	4.89

*Water elevation must be higher than backwater elevation.

RESTRICTIVE CULVERT WORKSHEET

JOB DATA:

Job Name:	ALGONQUIN RD INDUSTRIAL-PH 2
Job Number:	322-127-17
Designer:	PDL
Description	EXIST STM OUTFALL-18"

FLows ARE BASED ON THE FOLLOWING EQUATION:

$$Q = A \sqrt{\frac{H}{\frac{K_e + K_o}{2g} + \frac{2.87(n)^2 L}{\sqrt[3]{\phi^4}}}}$$

Q = FLOW (cfs)

A = AREA (sqr.ft.)

H = Head (ft.)

K_e & K_o = Entrance & Outlet Loss Coefficients

n = Manning's Roughness Coefficient

g = 32.2 ft/sec²

= diameter

ϕ

PIPE DATA:

Pipe Diameter (feet)	1.50	ft.
Pipe Area (sqr. ft)	1.767	sqr. ft.
Slope (ft./ft.)	0	
Length of Pipe (ft.)	10	ft.
Existing Invert Elevation	709.75	ft.
Backwater Elevation	711.25	ft. (Top of 18" pipe)
Manning's "n" value	0.013	
Entrance Loss Coefficient	0.50	
Outlet Loss Coefficient	1.00	

RATING TABLE:

Water Elevation (ft.)*	Head (ft.)	Q (cfs)
714.60	3.35	20.01
714.70	3.45	20.31
714.80	3.55	20.60
714.90	3.65	20.89
715.00	3.75	21.17
715.10	3.85	21.45
715.20	3.95	21.73
715.30	4.05	22.00
715.40	4.15	22.27
715.50	4.25	22.54
715.60	4.35	22.80

*Water elevation must be higher than backwater elevation.

ORIFICE WORKSHEET

Job Name:	ALGONQUIN RD INDUSTRIAL-PH 1
Job Number:	322-127-17
Designer:	PDL
Description	PROPOSED ORIFICE IN EXIST 10" RCP

FLOWS ARE BASED ON THE FOLLOWING EQUATION:

$$Q = AC\sqrt{2gH}$$

Q = FLOW (cfs)
 A = AREA (sqr.ft.)
 C = Orifice Coefficient
 g = 32.2 ft/sec²
 H = Head (ft.)

ORIFICE DATA:

Orifice diameter(inches)	3.125 inches
Orifice area(square feet)	0.053 sqr. ft.
Proposed invert elevation	711.12 ft.
Centerline of flow	711.25 ft
Orifice coefficient	0.6

RATING TABLE:

Water Elevation (ft.)*	Head (ft.)	Q (cfs)
715.00	3.75	0.50
715.10	3.85	0.50
715.20	3.95	0.51
715.30	4.05	0.52
715.40	4.15	0.52
715.50	4.25	0.53
715.60	4.35	0.53
715.70	4.45	0.54
715.80	4.55	0.55
715.90	4.65	0.55
716.00	4.75	0.56
716.10	4.85	0.56

*Water elevation must be higher than centerline of flow

ORIFICE WORKSHEET

Job Name:	ALGONQUIN RD INDUSTRIAL-PH 2
Job Number:	322-127-17
Designer:	PDL
Description	PROPOSED ORIFICE IN EXIST 18" RCP

FLOWS ARE BASED ON THE FOLLOWING EQUATION:

$$Q = AC\sqrt{2gH}$$

Q = FLOW (cfs)
 A = AREA (sqr.ft.)
 C = Orifice Coefficient
 g = 32.2 ft/sec²
 H = Head (ft.)

ORIFICE DATA:

Orifice diameter(inches)	5.000 inches
Orifice area(square feet)	0.136 sqr. ft.
Proposed invert elevation	709.75 ft.
Centerline of flow	709.96 ft
Orifice coefficient	0.6

RATING TABLE:

Water Elevation (ft.)*	Head (ft.)	Q (cfs)
715.00	5.04	1.47
715.10	5.14	1.49
715.20	5.24	1.50
715.30	5.34	1.52
715.40	5.44	1.53
715.50	5.54	1.55
715.60	5.64	1.56
715.70	5.74	1.57
715.80	5.84	1.59
715.90	5.94	1.60
716.00	6.04	1.61
716.10	6.14	1.63

*Water elevation must be higher than centerline of flow

RWG ENGINEERING, LLC.

975 E. 22nd Street

Wheaton, IL 60189

(630) 774-9501

Detention Calculator
Modified Rational Method

TELEPHONE (630) 774-9501			DESCRIPTION		Arlington Heights - BASIN CALCULATION SHEETS	
					Technical Bulletin 70 (7.58 in. - 100 Year Rainfall)	
					STORAGE VOLUME WITH ALLOWABLE RELEASE RATE-PHASE 1 TEMPORARY	
DURATION	TIME	100 YR. INT	INFLOW RATE	STORED RATE	VOLUME	
(HOURS)	(MIN)	(IN/HR)	(CFS)	(CFS)	(ACRE-FT)	
0.50	30	5.60	35.81	34.48	1.44	Area of site in acres: 7.44
0.67	40	4.92	31.46	30.13	1.67	Trapped water area in acres: 0.00
0.83	50	4.24	27.11	25.78	1.79	Net area for release computation in acres: 0.00
1.00	60	3.56	22.77	21.44	1.79	Allowable release rate in CFS: 1.33
1.50	90	2.90	18.55	17.22	2.15	Unrestricted release rate in CFS: 0.00
2.00	120	2.24	14.32	12.99	2.17	Bypass release rate in CFS: 0.00
3.00	180	1.62	10.36	9.03	2.26	Total allowable release in CFS: 1.33
4.00	240	1.40	8.93	7.60	2.53	Developed runoff coefficient: 0.86
5.00	300	1.17	7.50	6.17	2.57	
6.00	360	0.95	6.08	4.75	2.37	Maximum volume in Acre-Ft = 2.60
7.00	420	0.88	5.65	4.32	2.52	
8.00	480	0.82	5.22	3.89	2.60	
9.00	540	0.75	4.80	3.47	2.60	<===
10.00	600	0.68	4.37	3.04	2.53	
11.00	660	0.62	3.94	2.61	2.40	
12.00	720	0.55	3.52	2.19	2.19	
13.00	780	0.52	3.35	2.02	2.18	
14.00	840	0.50	3.18	1.85	2.15	
15.00	900	0.47	3.01	1.68	2.09	Phase 1:
16.00	960	0.44	2.84	1.51	2.01	Total Tributary Area after Phase 1 = 7.436 ac.
17.00	1020	0.42	2.66	1.33	1.89	Release rate = 1.33 cfs
18.00	1080	0.39	2.49	1.16	1.75	
19.00	1140	0.38	2.42	1.09	1.72	
20.00	1200	0.37	2.34	1.01	1.69	
21.00	1260	0.36	2.27	0.94	1.65	
22.00	1320	0.34	2.20	0.87	1.59	
23.00	1380	0.33	2.12	0.79	1.52	
24.00	1440	0.32	2.05	0.72	1.43	
		% of site	"C" Factor	Composite "C"		
Open Water Area		0.00	1.00	0.00		
Impervious Area		80.00	0.95	0.76		
Pervious Area		20.00	0.50	0.10		
Total :		100.00		0.86		

RWG ENGINEERING, LLC.

975 E. 22nd Street

Wheaton, IL 60189

(630) 774-9501

Detention Calculator
Modified Rational Method

TELEPHONE (630) 774-9501			DESCRIPTION		Arlington Heights - BASIN CALCULATION SHEETS		
					Technical Bulletin 70 (7.58 in. - 100 Year Rainfall)		
					STORAGE VOLUME WITH ALLOWABLE RELEASE RATE-PHASE 1 BUILD-OUT		
DURATION	TIME	100 YR. INT	INFLOW RATE	STORED RATE	VOLUME		
(HOURS)	(MIN)	(IN/HR)	(CFS)	(CFS)	(ACRE-FT)		
0.50	30	5.60	34.62	33.38	1.39	Area of site in acres:	6.93
0.67	40	4.92	30.41	29.17	1.62	Trapped water area in acres:	0.00
0.83	50	4.24	26.21	24.97	1.73	Net area for release computation in acres:	0.00
1.00	60	3.56	22.01	20.77	1.73	Allowable release rate in CFS:	1.24
1.50	90	2.90	17.93	16.69	2.09	Unrestricted release rate in CFS:	0.00
2.00	120	2.24	13.85	12.61	2.10	Bypass release rate in CFS:	0.00
3.00	180	1.62	10.01	8.77	2.19	Total allowable release in CFS:	1.24
4.00	240	1.40	8.63	7.39	2.46	Developed runoff coefficient:	0.89
5.00	300	1.17	7.25	6.01	2.51		
6.00	360	0.95	5.87	4.63	2.32	Maximum volume in Acre-Ft =	2.55
7.00	420	0.88	5.46	4.22	2.46		
8.00	480	0.82	5.05	3.81	2.54		
9.00	540	0.75	4.64	3.40	2.55	<===	
10.00	600	0.68	4.22	2.98	2.49		
11.00	660	0.62	3.81	2.57	2.36		
12.00	720	0.55	3.40	2.16	2.16		
13.00	780	0.52	3.24	2.00	2.16		
14.00	840	0.50	3.07	1.83	2.14		
15.00	900	0.47	2.91	1.67	2.08	Phase 1:	
16.00	960	0.44	2.74	1.50	2.00	Total Tributary Area after development = 6.934 ac.	
17.00	1020	0.42	2.58	1.34	1.89	Release rate = 1.24 cfs	
18.00	1080	0.39	2.41	1.17	1.76		
19.00	1140	0.38	2.34	1.10	1.74		
20.00	1200	0.37	2.27	1.03	1.71		
21.00	1260	0.36	2.19	0.95	1.67		
22.00	1320	0.34	2.12	0.88	1.62		
23.00	1380	0.33	2.05	0.81	1.55		
24.00	1440	0.32	1.98	0.74	1.48		
		% of site	"C" Factor	Composite "C"			
Open Water Area		0.00	1.00	0.00			
Impervious Area		87.00	0.95	0.83			
Pervious Area		13.00	0.50	0.07			
Total :		100.00		0.89			

RWG ENGINEERING, LLC.

975 E. 22nd Street

Wheaton, IL 60189

(630) 774-9501

Detention Calculator
Modified Rational Method

TELEPHONE (630) 774-9501			DESCRIPTION		Arlington Heights - BASIN CALCULATION SHEETS	
Technical Bulletin 70 (7.58 in. - 100 Year Rainfall)						
STORAGE VOLUME WITH ALLOWABLE RELEASE RATE-PHASE 2						
DURATION	TIME	100 YR. INT	INFLOW RATE	STORED RATE	VOLUME	
(HOURS)	(MIN)	(IN/HR)	(CFS)	(CFS)	(ACRE-FT)	
0.50	30	5.60	42.93	41.39	1.72	Area of site in acres: 8.56
0.67	40	4.92	37.72	36.18	2.01	Trapped water area in acres: 0.00
0.83	50	4.24	32.50	30.96	2.15	Net area for release computation in acres: 0.00
1.00	60	3.56	27.29	25.75	2.15	Allowable release rate in CFS: 1.54
1.50	90	2.90	22.23	20.69	2.59	Unrestricted release rate in CFS: 0.00
2.00	120	2.24	17.17	15.63	2.61	Bypass release rate in CFS: 0.00
3.00	180	1.62	12.42	10.88	2.72	Total allowable release in CFS: 1.54
4.00	240	1.40	10.71	9.17	3.06	Developed runoff coefficient: 0.90
5.00	300	1.17	8.99	7.45	3.11	
6.00	360	0.95	7.28	5.74	2.87	Maximum volume in Acre-Ft = 3.16
7.00	420	0.88	6.77	5.23	3.05	
8.00	480	0.82	6.26	4.72	3.15	
9.00	540	0.75	5.75	4.21	3.16	<===
10.00	600	0.68	5.24	3.70	3.08	
11.00	660	0.62	4.73	3.19	2.92	
12.00	720	0.55	4.22	2.68	2.68	
13.00	780	0.52	4.01	2.47	2.68	
14.00	840	0.50	3.81	2.27	2.65	
15.00	900	0.47	3.60	2.06	2.58	Phase 2:
16.00	960	0.44	3.40	1.86	2.48	Total Tributary Area after development = 8.556 ac.
17.00	1020	0.42	3.19	1.65	2.34	Release rate = 1.54 cfs
18.00	1080	0.39	2.99	1.45	2.17	
19.00	1140	0.38	2.90	1.36	2.15	
20.00	1200	0.37	2.81	1.27	2.12	
21.00	1260	0.36	2.72	1.18	2.07	
22.00	1320	0.34	2.63	1.09	2.00	
23.00	1380	0.33	2.54	1.00	1.92	
24.00	1440	0.32	2.45	0.91	1.83	
		% of site	"C" Factor	Composite "C"		
Open Water Area		0.00	1.00	0.00		
Impervious Area		88.00	0.95	0.84		
Pervious Area		12.00	0.50	0.06		
Total :		100.00		0.90		

RWG ENGINEERING, LLC.

975 E. 22nd Street

Wheaton, IL 60189

(630) 774-9501

Detention Calculator
Modified Rational Method

TELEPHONE (630) 774-9501			DESCRIPTION		Arlington Heights - BASIN CALCULATION SHEETS		
					Technical Bulletin 70 (7.58 in. - 100 Year Rainfall)		
					STORAGE VOLUME WITH DESIGN RELEASE RATE-PHASE 1 TEMPORARY		
DURATION	TIME	100 YR. INT	INFLOW RATE	STORED RATE	VOLUME		
(HOURS)	(MIN)	(IN/HR)	(CFS)	(CFS)	(ACRE-FT)		
0.50	30	5.60	35.81	34.60	1.44	Area of site in acres:	7.44
0.67	40	4.92	31.46	30.25	1.68	Trapped water area in acres:	0.00
0.83	50	4.24	27.11	25.90	1.80	Net area for release computation in acres:	0.00
1.00	60	3.56	22.77	21.56	1.80	Design release rate in CFS:	1.21
1.50	90	2.90	18.55	17.34	2.17	Unrestricted release rate in CFS:	0.00
2.00	120	2.24	14.32	13.11	2.19	Bypass release rate in CFS:	0.00
3.00	180	1.62	10.36	9.15	2.29	Total allowable release in CFS:	1.21
4.00	240	1.40	8.93	7.72	2.57	Developed runoff coefficient:	0.86
5.00	300	1.17	7.50	6.29	2.62		
6.00	360	0.95	6.08	4.87	2.43	Maximum volume in Acre-Ft =	2.69
7.00	420	0.88	5.65	4.44	2.59		
8.00	480	0.82	5.22	4.01	2.68		
9.00	540	0.75	4.80	3.59	2.69	<===	
10.00	600	0.68	4.37	3.16	2.63		
11.00	660	0.62	3.94	2.73	2.51		
12.00	720	0.55	3.52	2.31	2.31		
13.00	780	0.52	3.35	2.14	2.31		
14.00	840	0.50	3.18	1.97	2.29		
15.00	900	0.47	3.01	1.80	2.24	Phase 1:	
16.00	960	0.44	2.84	1.63	2.17	Total Tributary Area after Phase 1 = 7.436 ac.	
17.00	1020	0.42	2.66	1.45	2.06	Release rate = 1.21 cfs	
18.00	1080	0.39	2.49	1.28	1.93		
19.00	1140	0.38	2.42	1.21	1.91		
20.00	1200	0.37	2.34	1.13	1.89		
21.00	1260	0.36	2.27	1.06	1.86		
22.00	1320	0.34	2.20	0.99	1.81		
23.00	1380	0.33	2.12	0.91	1.75		
24.00	1440	0.32	2.05	0.84	1.67		
		% of site	"C" Factor	Composite "C"			
Open Water Area		0.00	1.00	0.00			
Impervious Area		80.00	0.95	0.76			
Pervious Area		20.00	0.50	0.10			
Total :		100.00		0.86			

RWG ENGINEERING, LLC.

975 E. 22nd Street

Wheaton, IL 60189

(630) 774-9501

Detention Calculator
Modified Rational Method

TELEPHONE (630) 774-9501			DESCRIPTION			Arlington Heights - BASIN CALCULATION SHEETS	
						Technical Bulletin 70 (7.58 in. - 100 Year Rainfall)	
						STORAGE VOLUME WITH DESIGN RELEASE RATE-PHASE 1 BUILD-OUT	
DURATION	TIME	100 YR. INT	INFLOW RATE	STORED RATE	VOLUME		
(HOURS)	(MIN)	(IN/HR)	(CFS)	(CFS)	(ACRE-FT)		
0.50	30	5.60	34.62	33.41	1.39	Area of site in acres:	6.93
0.67	40	4.92	30.41	29.20	1.62	Trapped water area in acres:	0.00
0.83	50	4.24	26.21	25.00	1.74	Net area for release computation in acres:	0.00
1.00	60	3.56	22.01	20.80	1.73	Design release rate in CFS:	1.21
1.50	90	2.90	17.93	16.72	2.09	Unrestricted release rate in CFS:	0.00
2.00	120	2.24	13.85	12.64	2.11	Bypass release rate in CFS:	0.00
3.00	180	1.62	10.01	8.80	2.20	Total allowable release in CFS:	1.21
4.00	240	1.40	8.63	7.42	2.47	Developed runoff coefficient:	0.89
5.00	300	1.17	7.25	6.04	2.52		
6.00	360	0.95	5.87	4.66	2.33	Maximum volume in Acre-Ft =	2.57
7.00	420	0.88	5.46	4.25	2.48		
8.00	480	0.82	5.05	3.84	2.56		
9.00	540	0.75	4.64	3.43	2.57	<===	
10.00	600	0.68	4.22	3.01	2.51		
11.00	660	0.62	3.81	2.60	2.39		
12.00	720	0.55	3.40	2.19	2.19		
13.00	780	0.52	3.24	2.03	2.19		
14.00	840	0.50	3.07	1.86	2.17		
15.00	900	0.47	2.91	1.70	2.12	Phase 1:	
16.00	960	0.44	2.74	1.53	2.04	Total Tributary Area after development = 6.934 ac.	
17.00	1020	0.42	2.58	1.37	1.93	Release rate = 1.21 cfs	
18.00	1080	0.39	2.41	1.20	1.80		
19.00	1140	0.38	2.34	1.13	1.79		
20.00	1200	0.37	2.27	1.06	1.76		
21.00	1260	0.36	2.19	0.98	1.72		
22.00	1320	0.34	2.12	0.91	1.67		
23.00	1380	0.33	2.05	0.84	1.61		
24.00	1440	0.32	1.98	0.77	1.54		
		% of site	"C" Factor	Composite "C"			
Open Water Area		0.00	1.00	0.00			
Impervious Area		87.00	0.95	0.83			
Pervious Area		13.00	0.50	0.07			
Total :		100.00		0.89			

RWG ENGINEERING, LLC.
975 E. 22nd Street
Wheaton, IL 60189
(630) 774-9501

Detention Calculator
Modified Rational Method

TELEPHONE (630) 774-9501			DESCRIPTION			Arlington Heights - BASIN CALCULATION SHEETS	
						Technical Bulletin 70 (7.58 in. - 100 Year Rainfall)	
						STORAGE VOLUME WITH DESIGN RELEASE RATE-PHASE 2	
DURATION	TIME	100 YR. INT	INFLOW RATE	STORED RATE	VOLUME		
(HOURS)	(MIN)	(IN/HR)	(CFS)	(CFS)	(ACRE-FT)		
0.50	30	5.60	42.93	41.40	1.73	Area of site in acres:	8.56
0.67	40	4.92	37.72	36.19	2.01	Trapped water area in acres:	0.00
0.83	50	4.24	32.50	30.97	2.15	Net area for release computation in acres:	0.00
1.00	60	3.56	27.29	25.76	2.15	Design release rate in CFS:	1.53
1.50	90	2.90	22.23	20.70	2.59	Unrestricted release rate in CFS:	0.00
2.00	120	2.24	17.17	15.64	2.61	Bypass release rate in CFS:	0.00
3.00	180	1.62	12.42	10.89	2.72	Total allowable release in CFS:	1.53
4.00	240	1.40	10.71	9.18	3.06	Developed runoff coefficient:	0.90
5.00	300	1.17	8.99	7.46	3.11		
6.00	360	0.95	7.28	5.75	2.88	Maximum volume in Acre-Ft =	3.16
7.00	420	0.88	6.77	5.24	3.06		
8.00	480	0.82	6.26	4.73	3.15		
9.00	540	0.75	5.75	4.22	3.16	<===	
10.00	600	0.68	5.24	3.71	3.09		
11.00	660	0.62	4.73	3.20	2.93		
12.00	720	0.55	4.22	2.69	2.69		
13.00	780	0.52	4.01	2.48	2.69		
14.00	840	0.50	3.81	2.28	2.66		
15.00	900	0.47	3.60	2.07	2.59	Phase 2:	
16.00	960	0.44	3.40	1.87	2.49	Total Tributary Area after development = 8.556 ac.	
17.00	1020	0.42	3.19	1.66	2.36	Release rate = 1.53 cfs	
18.00	1080	0.39	2.99	1.46	2.19		
19.00	1140	0.38	2.90	1.37	2.17		
20.00	1200	0.37	2.81	1.28	2.13		
21.00	1260	0.36	2.72	1.19	2.09		
22.00	1320	0.34	2.63	1.10	2.02		
23.00	1380	0.33	2.54	1.01	1.94		
24.00	1440	0.32	2.45	0.92	1.85		
		% of site	"C" Factor	Composite "C"			
Open Water Area		0.00	1.00	0.00			
Impervious Area		88.00	0.95	0.84			
Pervious Area		12.00	0.50	0.06			
Total :		100.00		0.90			

Runoff Curve Number

By: mrm Date: 10/12/2017
Checked: mrm Date: 10/12/2017

Circle One: Present Developed Description: 7.436-Acre Site - Phase 1 - temp cond

Soil Name and Hydrologic Group (Appendix A)	Cover Description (cover type, treatment, and hydrologic condition; percent impervious; unconnected/connected impervious area ratio)	Curve Number	Area	Product of Curve Number and Area
			☒ acres	
			☐ sq. mi.	
			☐ %	
C	Pervious Area - Open Space, Good Condition	74	1.534	113.516
C	Permeable Pavement	91	0.000	0
C	Impervious Area - Building	98	5.848	573.104
C	Impervious Area - Open Water	100	0.054	5.4
Totals =			7.436	692.02

$$\text{CN (weighted)} = \frac{\text{total product}}{\text{total area}} = \frac{692.02}{7.436} = \underline{93.063}$$

Use CN =

93

RUNOFF CURVE NUMBER ADJUSTMENT CALCULATOR

Site Information:

Total Site Area, A_w (ac) = 7.436

Total Impervious Area, A_i (ac) = 5.902

Runoff, R (in) = 6.75

P = rainfall depth (in) = 7.58

CN = 93

S = 0.75

Runoff Volume Over Watershed, V_w (ac-ft) = 4.18

Volume of GI Provided:

Volume Control Storage, V_r = 0.49 ac-ft

1" of volume over impervious area

Additional Volume, V_{GI} = 0.00 ac-ft

Additional volume over the required 1"

Adjusted Volume Over Watershed, $V_{Adj} = V_w - V_r - V_{GI}$

V_{Adj} (ac-ft) = 3.69

Adjusted Runoff Over Watershed, $R_{Adj} = V_{Adj} \frac{A_w}{A_i}$

R_{Adj} (in) = 5.95

S_{Adj} = 1.60

Adjusted CN for detention calcs, CN_{Adj} =

86.22

*Blue values are entered by user


Enter Site Area: acres

*Blue Values are entered by user

Enter Reduced Curve Number for Site:

Estimated Required Detention Volume: acre-feet

DETENTION VOLUME VS REDUCED CURVE NUMBER*



*ADJUSTED FOR VOLUME CONTROL STORAGE PROVIDED, BASED ON RELEASE RATE OF 0.30 CFS/ACRE

Runoff Curve Number

Project:	Phase 1 - Final
Location:	Arlington Heights, Cook County, IL
File:	CN 101217.xlsx

By: mrm Date: 10/12/2017
Checked: mrm Date: 10/12/2017

Circle One: Present Developed

Description: 6.934-Acre Site - Phase 1 - build out

Soil Name and Hydrologic Group (Appendix A)	Cover Description (cover type, treatment, and hydrologic condition; percent impervious; unconnected/connected impervious area ratio)	Curve Number	Area	Product of Curve Number and Area
			☒ acres	
			☐ sq. mi.	
			☐ %	
C	Pervious Area - Open Space, Good Condition	74	0.918	67.932
C	Permeable Pavement	91	0.000	0
C	Impervious Area - Building	98	5.962	584.276
C	Impervious Area - Open Water	100	0.054	5.4
Totals =			6.934	657.608

$$\text{CN (weighted)} = \frac{\text{total product}}{\text{total area}} = \frac{657.608}{6.934} = \underline{94.838}$$

Use CN =

95

RUNOFF CURVE NUMBER ADJUSTMENT CALCULATOR

Site Information:

Total Site Area, A_w (ac) = 6.934

Total Impervious Area, A_i (ac) = 6.016

Runoff, R (in) = 6.98

P = rainfall depth (in) = 7.58

CN = 95

S = 0.53

Runoff Volume Over Watershed, V_w (ac-ft) = 4.04

Volume of GI Provided:

Volume Control Storage, V_r = 0.50 ac-ft

1" of volume over impervious area

Additional Volume, V_{GI} = 0.00 ac-ft

Additional volume over the required 1"

Adjusted Volume Over Watershed, $V_{ADJ} = V_w + V_r + V_{GI}$

V_{ADJ} (ac-ft) = 3.53

Adjusted Runoff Over Watershed, $R_{ADJ} = V_{ADJ} \frac{A_w}{A_w}$

R_{ADJ} (in) = 6.12

S_{ADJ} = 1.41

Adjusted CN for detention calcs, $CN_{ADJ} =$

87.68


*Blue values are entered by user

Enter Site Area: acres

*Blue Values are entered by user

Enter Reduced Curve Number for Site:

Estimated Required Detention Volume: acre-feet



Runoff Curve Number

Project:	Phase 2 - Final
Location:	Arlington Heights, Cook County, IL
File:	CN 101217.xlsx

By: mrm Date: 10/12/2017
Checked: mrm Date: 10/12/2017

Circle One: Present Developed

Description: 8.556-Acre Site - Phase 2 - build out

Soil Name and Hydrologic Group (Appendix A)	Cover Description (cover type, treatment, and hydrologic condition; percent impervious; unconnected/connecting impervious area ratio)	Curve Number	Area	Product of Curve Number and Area
			☒ acres	
			☐ sq. mi.	
			☐ %	
C	Pervious Area - Open Space, Good Condition	74	1.042	77.108
C	Permeable Pavement	91	0.000	0
C	Impervious Area - Building	98	7.514	736.372
C	Impervious Area - Open Water	100	0.000	0
		Totals =	8.556	813.48

$$\text{CN (weighted)} = \frac{\text{total product}}{\text{total area}} = \frac{813.48}{8.556} = \underline{95.077}$$

Use CN =

95

RUNOFF CURVE NUMBER ADJUSTMENT CALCULATOR

Site Information:

Total Site Area, A_w (ac) = 8.556

Total Impervious Area, A_i (ac) = 7.514

Runoff, R (in) = 6.98

P = rainfall depth (in) = 7.58

CN = 95

S = 0.53

Runoff Volume Over Watershed, V_w (ac-ft) = 4.98

Volume of GI Provided:

Volume Control Storage, V_r = 0.63 ac-ft

1" of volume over impervious area

Additional Volume, V_{GI} = 0.00 ac-ft

Additional volume over the required 1"

Adjusted Volume Over Watershed, $V_{ADJ} = V_w - V_r - V_{GI}$

V_{ADJ} (ac-ft) = 4.35

Adjusted Runoff Over Watershed, $R_{ADJ} = \frac{V_{ADJ}}{A_w}$

R_{ADJ} (in) = 6.10

S_{ADJ} = 1.43

Adjusted CN for detention calcs, $CN_{ADJ} =$

87.51

* Blue values are entered by user

Enter Site Area: acres

*Blue Values are entered by user

Enter Reduced Curve Number for Site:

Estimated Required Detention Volume: acre-feet

DETENTION VOLUME VS REDUCED CURVE NUMBER *




TABLE 2
ARLINGTON HEIGHTS INDUSTRIAL
SUMMARY OF STORMWATER STORAGE PROVIDED

PHASE 1 - NORTH

<u>Basin</u>	<u>Description</u>	Det Storage (Ac-Ft)	Volume Control <u>Storage (Ac-Ft)</u>
N-1	Existing Pond	0.370	0
N-2	Modified Pond	1.115	0.095
N-3	Underground	0.500	0.400
N-4?	Truck Dock Area	0.579	0
	Pipe Storage	<u>0.117</u>	<u>0</u>
	Total Volume:	2.681	0.495

PHASE 2 - SOUTH

<u>Basin</u>	<u>Description</u>	Det Storage (Ac-Ft)	Volume Control <u>Storage (Ac-Ft)</u>
S-1	New Pond	0.704	0.049
S-2	Underground-W	0.938	0.429
S-3	Underground-SE	0.286	0.051
S-4	Underground-E	0.226	0.041
	Truck Dock Area	0.953	0
	Pipe Storage	<u>0.101</u>	<u>0</u>
	Total Volume:	3.208	0.569

Cut/Fill Report-- STORAGE VOLUMES PROVIDED

Generated: 2017-10-18 09:59:53

By user: RWGENGSTA07

Drawing: S:\32212717 - HP Arlington Heights Industrial\300_Engineering\310_CADD\Exhibits\S\32212717 - HP Arlington Heights Industrial\300_Engineering\310_CADD\Exhibits\322_BASE_Basin.dwg

Volume Summary							
Name	Type	Cut Factor	Fill Factor	2d Area (Sq. Ft.)	Cut (Cu. Yd.)	Fill (Cu. Yd.)	Net (Cu. Yd.)
EX Basin N-1 (Det) NWL 710.65	full	0.000	1.000	4405.29	0.00*	597.51	597.51*
Basin N-2 (Det) NWL 710.2	full	0.000	1.000	12790.21	0.00*	1798.88	1798.88*
Basin N-2 (Vol Control)	full	0.000	1.000	5316.58	0.00*	152.88	152.88*
North Truck Dock	full	0.000	1.000	52639.96	0.00*	934.61	934.61*
Basin S-1 (Det) NWL 709.8	full	0.000	1.000	9218.35	0.00*	1134.98	1134.98*
Basin S-1 (Vol Control)	full	0.000	1.000	3112.46	0.00*	78.87	78.87*
South Truck Dock	full	0.000	1.000	85783.42	0.00*	1537.32	1537.32*

Ac - Ft.

0.370

1.115

0.095

0.579

0.704

0.049

0.953

Totals				
	2d Area (Sq. Ft.)	Cut (Cu. Yd.)	Fill (Cu. Yd.)	Net (Cu. Yd.)
Total	173266.27	0.00*	6235.04	6235.04*

* Value adjusted by cut or fill factor other than 1.0

ARLINGTON HEIGHTS INDUSTRIAL
DETENTION STORAGE IN STORM SEWER SYSTEM
BELOW 715.4 HWL

PHASE 1 - NORTH

Pipe Storage:

Pipe Size (Inches)	Length (Feet)	Area (Sq Ft)	Volume (Cu Ft)
10	284	0.545	154.819
12	353	0.785	277.105
15	334	1.227	409.672
18	535	1.766	944.944
21	191	2.404	459.176
24	348	3.140	1092.720
30	0	4.906	0.000
36	251	7.065	<u>1773.315</u>

Total Pipe Storage: 5111.751 0.117 Ac-Ft

PHASE 2 - SOUTH

Pipe Storage:

Pipe Size (Inches)	Length (Feet)	Area (Sq Ft)	Volume (Cu Ft)
10	302	0.545	164.632
12	301.5	0.785	236.678
15	325	1.227	398.633
18	341	1.766	602.291
21	0	2.404	0.000
24	182	3.140	571.480
30	405	4.906	1987.031
36	60	7.065	<u>423.900</u>

Total Pipe Storage: 4384.645 0.101 Ac-Ft

WEIR FLOW CALCULATIONS ARLINGTON HEIGHTS INDUSTRIAL


Designer:	PDL
Description:	100 YEAR-PHASE 1

BASED ON THE FOLLOWING EQUATION:

$$Q = \left[K \times \frac{2}{3} \times L \times (2g)^{0.5} \times H^{1.5} \right] + \frac{1}{2} \left[K \times \frac{8}{15} \times (2g)^{0.5} \times S_1 \times H^{2.5} \right] + \frac{1}{2} \left[K \times \frac{8}{15} \times (2g)^{0.5} \times S_2 \times H^{2.5} \right]$$

WHERE:

Q = DISCHARGE IN CFS
K = WEIR COEFFICIENT
L = LENGTH IN FEET
g = 32.2 FT/SEC
H = HEAD IN FEET
S1 = LEFT SIDE SLOPE
S2 = RIGHT SIDE SLOPE



WEIR DATA: OVERFLOW CHANNEL AA-AA

- | | | |
|--------------------------------|------|------|
| 1. LENGTH, L | 26.0 | FEET |
| 2. WEIR COEFFICIENT, K (K<1.0) | 0.57 | |
| 3. LEFT SIDE SLOPE, S (H:V) | 1 | : 1 |
| 4. RIGHT SIDE SLOPE, S (H:V) | 1 | : 1 |

5 RATING TABLE	HEAD (FEET)	DISCHARGE (CFS)
	0.20	7.14
	0.25	9.99
	0.30	13.15
	0.35	16.59
	0.40	20.31
	0.45	24.27
	0.50	28.46
	0.55	32.89
	0.60	37.53
	0.65	42.38

WEIR FLOW CALCULATIONS ARLINGTON HEIGHTS INDUSTRIAL


Designer:	PDL
Description:	100 YEAR-PHASE 2

BASED ON THE FOLLOWING EQUATION:

$$Q = \left[K \times \frac{2}{3} \times L \times (2g)^{0.5} \times H^{1.5} \right] + \frac{1}{2} \left[K \times \frac{8}{15} \times (2g)^{0.5} \times S_1 \times H^{2.5} \right] + \frac{1}{2} \left[K \times \frac{8}{15} \times (2g)^{0.5} \times S_2 \times H^{2.5} \right]$$

WHERE:

Q = DISCHARGE IN CFS
K = WEIR COEFFICIENT
L = LENGTH IN FEET
g = 32.2 FT/SEC
H = HEAD IN FEET
S1 = LEFT SIDE SLOPE
S2 = RIGHT SIDE SLOPE



WEIR DATA: OVERFLOW CHANNEL AA-AA

- | | | |
|--------------------------------|------|------|
| 1. LENGTH, L | 20.0 | FEET |
| 2. WEIR COEFFICIENT, K (K<1.0) | 0.50 | |
| 3. LEFT SIDE SLOPE, S (H:V) | 1 | : 4 |
| 4. RIGHT SIDE SLOPE, S (H:V) | 1 | : 4 |

5. RATING TABLE

HEAD (FEET)	DISCHARGE (CFS)
----------------	--------------------

0.30	8.90
0.35	11.23
0.40	13.75
0.45	16.44
0.50	19.29
0.55	22.30
0.60	25.46
0.65	28.77
0.70	32.21
0.75	35.79
0.80	39.51
0.85	43.35
0.90	47.32
0.95	51.42
1.00	55.64

STORM SEWER WORKSHEET

Designer: PDLDate: 09-22-17
Update:10-12-17

Description: PROPOSED ALGONQUIN ROAD
INDUSTRIAL PARCEL-PH 1 (NORTH)
ARLINGTON HEIGHTS, IL

FREQUENCY: 10 YR.* ROUGH. COEFF. 0.013 RUNOFF COEFF: Varies (See Below)

* TYPICAL 10 YR FREQUENCY, EXCEPT RUN FROM EX STR 28 TO UNDERGROUND
BASIN WHICH IS A 100 YEAR FREQUENCY-SEE BELOW

MH-MH	ADDED		TOTAL		C X A	TIME		I IN/HR	Q CFS	PIPE DIA IN	PIPE SLOPE %	VEL FPS	L FT	CAP CFS	COMMENTS
	"C"	AREA AC	"C"	AREA AC		FLOW MIN	T/C MIN								
East Run															
60-61	0.87	0.208	0.87	0.208	0.18	0.1	10.0	5.88	1.06	10.00	0.80	3.59	25	1.96	N13-Build-Out (Ph 2)
58-60	0.95	0.717	0.93	0.925	0.86	0.5	10.1	5.88	5.07	15.00	0.70	4.40	131	5.40	Add B8
56-58	0.85	0.201	0.92	1.126	1.03	0.5	10.6	5.88	6.07	18.00	0.40	3.76	122	6.64	N12/Str 59
54-56	0.84	0.153	0.91	1.279	1.16										N11/Str57
	0.95	0.719	0.92	1.998	1.84	0.4	11.2	5.68	10.48	21.00	0.50	4.66	123	11.20	Add B7
Ex28-54	0.83	0.098	0.92	2.096	1.93	0.2	11.6	5.68	10.94	21.00	0.50	4.66	68	11.20	N10/Str 55
Tributary Lateral Runs From South Curb Line															
58-59	0.85	0.201	0.85	0.201	0.171	0.1	10.0	5.88	1.00	10.00	0.80	3.59	13	1.96	N12
56-57	0.84	0.153	0.84	0.153	0.129	0.1	10.0	5.88	0.76	10.00	0.80	3.59	13	1.96	N11
54-55	0.83	0.098	0.83	0.098	0.081	0.1	10.0	5.88	0.48	10.00	0.80	3.59	13	1.96	N10
62-63	0.78	0.093	0.78	0.093	0.073	0.1	10.0	5.88	0.43	10.00	1.25	4.49	16	2.45	N9
North Parking Area-Restrictor MH to Basin N-2 -10 Year Frequency															
Ex 28-62	0.92	2.096	0.92	2.096	1.93	0.1	11.6	5.68	10.94	36.00	0.03	1.63	10	11.55	From Str 54
62-64	0.77	0.093	0.91	2.189	2.00										N9
	0.95	0.261	0.92	2.450	2.25	0.6	11.7	5.68	12.75	36.00	0.04	1.89	70	13.34	Add B11
64-65	0.82	0.283	0.91	2.733	2.48	0.8	12.3	5.47	13.55	36.00	0.05	2.11	106	14.91	N8
65-68	0.84	0.186	0.90	2.919	2.63	0.5	13.2	5.26	13.85	24.00	0.38	4.44	128	13.95	N6
68-71	0.82	0.054	0.90	2.973	2.68										N4
	0.76	0.096	0.90	3.069	2.75	0.3	13.6	5.26	14.47	24.00	0.41	4.61	82	14.49	Add N1
71-70	0.93	0.088	0.90	3.157	2.83	0.2	13.9	5.26	14.90	24.00	0.44	4.78	51	15.01	N2
70-74	0.89	0.086	0.90	3.243	2.91	0.2	14.1	5.05	14.69	24.00	0.44	4.78	54	15.01	N3
74-73	0.95	0.073	0.90	3.316	2.98	0.1	14.3	5.05	15.04	24.00	0.45	4.83	33	15.18	Add B9
North Parking Area-Restrictor MH to Basin N-3 -100 Year Frequency															
Ex 28-62	0.92	2.096	0.92	2.096	1.93	0.1	11.6	9.66	18.60	36.00	0.08	2.67	10	18.86	From Str 54
62-64	0.77	0.093	0.91	2.189	2.00										N9
	0.95	0.261	0.92	2.450	2.25	0.4	11.7	9.66	21.69	36.00	0.11	3.13	70	22.12	Add B11
64-65	0.82	0.283	0.91	2.733	2.48	0.5	12.0	9.29	23.02	36.00	0.12	3.27	106	23.10	N8
65-66	0.84	0.186	0.90	2.919	2.63	0.3	12.6	9.29	24.47	36.00	0.13	3.40	65	24.05	N6
66-Basins	0.88	0.215	0.90	3.134	2.82		12.9	9.29	26.23	18.00	6.25	14.86	5	26.26	N7

Req'd H	Total H	Elev
0.003	1.517	713.72 OK, Rim @ 715.55
	1.514	713.71
0.028	1.514	713.71 OK, Rim @ 715.20
0.053	1.486	713.69
0.486	1.433	713.63 (Flow to Basin N-3 Begins at 713.41-
	0.947	713.15 Would Reduce Flow To Basin N-2
0.336	0.947	713.15 Not Considered)
0.224	0.611	712.81
0.238	0.386	712.59
0.149	0.149	712.35 712.20 (Pipe Crown @ FES)

Req'd H	Total H	Elev
0.008	0.609	715.48 OK, Rim @ 715.55
	0.601	715.47
0.077	0.601	715.47 Rim @ 715.20 (Overflow @ 715.4)
0.127	0.524	715.39
0.085	0.397	715.27
0.313	0.313	715.18 714.87 Crown Basin N-3

FREQUENCY: 10 YR.* ROUGH. COEFF. 0.013 RUNOFF COEFF: Varies (See Below)

* TYPICAL 10 YR FREQUENCY, EXCEPT RUN FROM EX STR 28 TO UNDERGROUND
BASIN WHICH IS A 100 YEAR FREQUENCY-SEE BELOW

MH-MH	ADDED		TOTAL		C X A	TIME		I IN/HR	Q CFS	PIPE DIA IN	PIPE SLOPE %	VEL FPS	L FT	CAP CFS	COMMENTS
	"C"	AREA AC	"C"	AREA AC		FLOW MIN	T/C MIN								
North Parking-Tributary lateral Runs From Curb Line															
68-69	0.76	0.096	0.76	0.096	0.07	0.1	10.0	5.88	0.43	10.00	2.60	6.48	53	3.53	N1
Str 67	0.93	0.119	0.93	0.119	0.11		10.0	5.88	0.65						N5-Direct to Basin
West Dock - Parallel Run (Design Gradients)															
85-85A	0.50	0.230	0.50	0.230	0.12	0.1	10.0	5.88	0.68	8.00	0.50	2.45	22	0.85	N22-Temp-Ph 1 only
84-85	0.95	0.131	0.66	0.361	0.24	0.7	10.0	5.88	1.41	12.00	0.20	2.03	82	1.59	Add B6-Temp
84-85	0.95	0.262	0.95	0.262	0.25	0.7	10.0	5.88	1.46	12.00	0.20	2.03	82	1.59	B6 Build Out-Use
83-84	0.89	0.363	0.92	0.625	0.57	0.4	10.7	5.88	3.36	15.00	0.15	2.04	52	2.50	N21
82-83	0.95	0.120	0.92	0.745	0.69	0.3	11.1	5.68	3.90	15.00	0.15	2.04	40	2.50	N20
86-82	0.95	0.130	0.93	0.875	0.81										N19
	0.95	0.524	0.93	1.399	1.31	0.5	11.4	5.68	7.43	15.00	0.17	2.17	59	2.66	Add B7
76-86									7.43	18.00	0.15	2.30	232	4.07	
80-81	0.95	0.121	0.95	0.121	0.11	0.3	10.0	5.88	0.68	12.00	0.22	2.13	40	1.67	N18
79-80	0.95	0.130	0.95	0.251	0.24	0.4	10.3	5.88	1.40	12.00	0.22	2.13	50	1.67	N17
78-79	0.95	0.122	0.95	0.373	0.35	0.3	10.7	5.88	2.08	15.00	0.15	2.04	40	2.50	N16
77-78	0.95	0.168	0.95	0.541	0.51										N15
	0.95	0.485	0.95	1.026	0.97	0.4	11.0	5.68	5.54	18.00	0.15	2.30	52	4.07	Add B8
76-77	0.92	0.210	0.94	1.236	1.17	0.4	11.4	5.68	6.63	18.00	0.15	2.30	59	4.07	N14
75-76	0.87	1.498	0.90	2.734	2.47	0.5	11.8	5.68	14.04	18.00	0.15	2.30	65	4.07	Add Run 76-86
West Dock - Parallel Run (Required Gradients)															
84-85	0.95	0.262	0.95	0.262	0.25	0.7	10.0	5.88	1.46	12.00	0.17	1.87	82	1.47	B6 Bild Out- Use
83-84	0.89	0.363	0.92	0.625	0.57	0.3	10.7	5.88	3.36	15.00	0.27	2.74	52	3.36	N21
82-83	0.95	0.120	0.92	0.745	0.69	0.2	11.0	5.68	3.90	15.00	0.37	3.20	40	3.93	N20
86-82	0.95	0.130	0.93	0.875	0.81										N19
	0.95	0.524	0.93	1.399	1.31	0.2	11.3	5.68	7.43	15.00	1.33	6.07	59	7.45	Add B2
76-86									7.43	18.00	0.50	4.20	232	7.43	
80-81	0.95	0.121	0.95	0.121	0.11	0.7	10.0	5.88	0.68	12.00	0.04	0.91	40	0.71	N18
79-80	0.95	0.130	0.95	0.251	0.24	0.5	10.7	5.88	1.40	12.00	0.16	1.81	50	1.43	N17
78-79	0.95	0.122	0.95	0.373	0.35	0.4	11.2	5.68	2.01	15.00	0.10	1.66	40	2.04	N16
77-78	0.95	0.168	0.95	0.541	0.51										N15
	0.95	0.485	0.95	1.026	0.97	0.3	11.6	5.68	5.54	18.00	0.28	3.15	52	5.56	Add B3

Above worst case. Allowabe/design release rate from site, as well as
flow to Basin N-2 via 24" RCP not deducted from above flow review to
Basin N-3

Req'd H	Total H	Elev	
0.140	2.202	713.90	OK, Rim @ 714.05
0.148	2.062	713.76	
0.000	1.914	713.61	
0.785	1.914	713.61	
	1.129	712.83	(Str 76 below)
0.016	1.646	713.35	
0.080	1.630	713.33	
0.040	1.550	713.25	
0.000	1.510	713.21	
0.146	1.510	713.21	

FREQUENCY: 10 YR.* ROUGH. COEFF. 0.013 RUNOFF COEFF: Varies (See Below)

* TYPICAL 10 YR FREQUENCY, EXCEPT RUN FROM EX STR 28 TO UNDERGROUND
BASIN WHICH IS A 100 YEAR FREQUENCY-SEE BELOW

MH-MH	ADDED		TOTAL		C X A	TIME		I IN/HR	Q CFS	PIPE DIA IN	PIPE SLOPE %	VEL FPS	L FT	CAP CFS	COMMENTS
	"C"	AREA AC	"C"	AREA AC		FLOW MIN	T/C MIN								
76-77	0.92	0.210	0.94	1.236	1.17	0.3	11.9	5.68	6.63	18.00	0.40	3.76	59	6.64	N14
75-76	0.87	1.498	0.90	2.734	2.47	0.1	12.1	5.47	13.52	18.00	1.66	7.66	68	13.53	Add Run 76-86
Review Full Flow Velocity (Design Gradients) For Min 2.0 fps Velocity:										12.00	0.20	2.03		1.59	
										15.00	0.15	2.04		2.50	
										18.00	0.15	2.30		4.07	
										24.00	0.10	2.28		7.15	
										36.00	0.10	2.98		21.09	
Roof Drains															
B6	0.95	0.131	0.95	0.131	0.124	0.0	10.0	5.88	0.73	10.00	2.00	5.68	10	3.10	
B7	0.95	0.524	0.95	0.524	0.498	0.1	10.0	5.88	2.93	10.00	1.80	5.39	22	2.94	
B8	0.95	0.485	0.95	0.485	0.461	0.0	10.0	5.88	2.71	10.00	1.70	5.24	12	2.86	
B9	0.95	0.073	0.95	0.073	0.069	0.0	10.0	5.88	0.41	10.00	4.00	8.03	23	4.38	
B10	0.95	0.270	0.95	0.270	0.257	0.1	10.0	5.88	1.51	10.00	1.50	4.92	37	2.68	
B11	0.95	0.261	0.95	0.261	0.248	0.2	10.0	5.88	1.46	10.00	1.00	4.02	47	2.19	
B12	0.95	0.719	0.95	0.719	0.683	0.1	10.0	5.88	4.02	12.00	3.57	8.57	60	6.73	
B13	0.95	0.717	0.95	0.717	0.681	0.1	10.0	5.88	4.01	12.00	2.50	7.17	39	5.63	

0.236 1.365 713.06
1.129 1.129 712.83 711.70 (Pipe Crown @FES)

STORM SEWER WORKSHEET

Designer:	
Description:	Phase 2 East Section

FREQUENCY: 10 YR. ROUGH. COEFF. 0.013 RUNOFF COEFF: 0.50

[illegible]

tc	i
10	5.88
11	5.68
12	5.47
13	5.26
14	5.05
15	4.84
16	4.74
17	4.63
20	4.33

STORM SEWER WORKSHEET

Designer:

Description:Phase 2 West Section



FREQUENCY: 10 YR. ROUGH. COEFF. 0.013 RUNOFF COEFF: 0.50

MH-MH	ADDED		TOTAL		C X A	TIME		I IN/HR	Q CFS	PIPE DIA IN	PIPE SLOPE %	VEL FPS	L FT	CAP CFS	UPPER MH			LOWER MH			COMMENTS
	"C"	AREA AC	"C"	AREA AC		FLOW MIN	T/C MIN								RIM	CROWN	INV	RIM	CROWN	INV	
87-88	0.87	0.230	0.87	0.230	0.200	0.2	10	5.88	1.18	10.00	0.30	2.20	26	1.20	714.05	711.98	711.15	714.05	711.90	711.07	
88-89	0.95	0.116	0.90	0.346	0.310	0.4	10.2	5.88	1.82	15.00	0.15	2.04	52	2.50	714.05	712.32	711.07	714.05	712.24	710.99	
89-90	0.95	0.117	0.91	0.463	0.421	0.3	10.6	5.88	2.48	15.00	0.15	2.04	39	2.50	714.05	712.24	710.99	714.05	712.18	710.93	
B5-90	0.95	0.524																			
90-91	0.95	0.134	0.93	1.121	1.047	0.3	10.9	5.88	6.15	18.00	0.35	3.52	72	6.21	714.05	712.34	710.84	715.69	712.09	710.59	
91-96	0.00	0.000	0.93	1.121	1.047			5.88	6.15	24.00	0.08	2.04	182	6.40	715.69	712.59	710.59	715.60	712.44	710.44	
92-93	0.95	0.117	0.95	0.117	0.111	0.3	10	5.88	0.65	10.00	0.25	2.01	39	1.10	714.05	711.98	711.15	714.05	711.88	711.05	
93-94	0.95	0.134	0.95	0.251	0.238	0.4	10.3	5.88	1.40	15.00	0.15	2.04	52	2.50	714.05	712.30	711.05	714.05	712.22	710.97	
94-95	0.95	0.117	0.95	0.368	0.350	0.3	10.7	5.88	2.06	15.00	0.15	2.04	39	2.50	714.05	712.22	710.97	714.05	712.16	710.91	
B4-95	0.95	0.524																			
95-96	0.95	0.134	0.95	1.026	0.975	0.4	11.1	5.68	5.54	18.00	0.28	3.15	72	5.56	714.05	712.34	710.84	715.60	712.14	710.64	
96-103	0.00	0.000	0.94	2.147	2.021	1.6	11.4	5.68	11.48	30.00	0.10	2.64	260	12.97	715.60	712.94	710.44	715.46	712.68	710.18	
97-98	0.95	0.115	0.95	0.115	0.109	0.3	10	5.88	0.64	10.00	0.25	2.01	39	1.10	714.05	711.98	711.15	714.05	711.88	711.05	
98-99	0.95	0.134	0.95	0.249	0.237	0.3	10.3	5.88	1.39	10.00	0.40	2.54	52	1.39	714.05	711.88	711.05	714.05	711.68	710.84	
99-100	0.95	0.117	0.95	0.366	0.348	0.3	10.7	5.88	2.04	15.00	0.15	2.04	39	2.50	714.05	712.09	710.84	714.05	712.03	710.78	
100-101	0.95	0.134	0.95	0.500	0.475	0.4	11.0	5.68	2.70	15.00	0.18	2.23	52	2.74	714.05	712.03	710.78	714.05	711.94	710.69	
B3-101	0.95	0.486																			
101-102	0.95	0.099	0.95	1.085	1.031	0.1	11.4	5.68	5.85	18.00	0.31	3.31	26	5.85	714.05	712.19	710.69	714.05	712.11	710.61	
102-103	0.89	0.269	0.94	1.354	1.270	0.3	11.5	5.68	7.21	18.00	0.48	4.12	72	7.28	714.05	712.11	710.61	715.46	711.76	710.26	
103-104	0.00	0.000	0.94	3.501	3.291	0.6	11.8	5.68	18.70	30.00	0.21	3.83	145	18.80	715.46	712.68	710.18	716.78	712.38	709.88	
105-104	0.95	0.082	0.95	0.082	0.078	0.3	10	5.88	0.46	10.00	0.25	2.01	39	1.10	715.88	713.71	712.88	716.78	713.62	712.78	
B1-104	0.95	0.073																			
104-V	0.00	0.000	0.94	3.656	3.439	0.3	12.4	5.47	18.81	36.00	0.13	3.40	60	24.05	716.78	712.88	709.88	N/A	712.80	709.80	

tc	i
10	5.88
11	5.68
12	5.47
13	5.26
14	5.05
15	4.84
16	4.74
17	4.63
20	4.33

BOUNDARY AND TOPOGRAPHIC SURVEY

BY
GENTILE AND ASSOCIATES, INC.
PROFESSIONAL LAND SURVEYORS



	NO.	DATE	DESCRIPTION	BY
	3	8/07/2015	WATER MAIN GAS & TELL WORK NEEDED [CHECKED & OK'D]	MAG
	2	6/04/2015	SUBMITTAL OF THE INTERVIEW REVIEW FOR TOTAL OF THE 10% INTERVIEW REVIEW [OK'D]	MAG
	1	6/03/2015	CATCH BASIN WAS CHANGED TO AIR (1996) [CHECKED & OK'D]	MAG

BASE SCALE : 1 INCH = 50 FEET
DISTANCES ARE MARKED IN FEET AND DECIMAL PARTS THEREOF
ORDERED BY : RWC ENGINEERING LLC
DRAWN BY : MLC

DRAIN BY : _____
 CHECKED BY : _____
 SURVEYED BY : LR-RB-JS
 COMPARE ALL POINTS BEFORE BUILDING BY SAME AND AT ONCE REPORT
 ANY DIFFERENCE FOR BUILDING LINE AND OTHER RESTRICTIONS NOT
 SHOWN HEREON REFER TO YOUR ABSTRACT DEED, CONTRACT AND ZONING
 ORDINANCE.



ORDER NO. 17-20813- REV 3
SHEET 1 OF 3

STATE OF ILLINOIS
COUNTY OF DU PAGE
S.S.

WE, GENTILE AND ASSOCIATES, INC., HEREBY CERTIFY THAT A SURVEY HAS BEEN MADE AT AND UNDER MY DIRECTION, OF THE PROPERTY DESCRIBED ABOVE, AND THAT THE PLAT HEREON DRAWN IS A CORRECT REPRESENTATION OF SAID SURVEY. THIS PLAT CONFORMS TO THE MINIMUM STANDARD REQUIREMENTS FOR A BOUNDARY SURVEY.

JULY 27, 1917 A.D. 2017

BY : _____
ILLINOIS PROFESSIONAL LAND SURVEYOR NO. 2925
MY LICENSE EXPIRES NOVEMBER 30, 2018
ILLINOIS PROFESSIONAL DESIGN FIRM LICENSE NO. 184.002870



DRAINAGE AREA SUMMARY	
Parcel 1:	Area (ac):
1	0.20
2	1.15
3	0.19
4	0.12
5	0.16
6	0.93
7	0.10
8	1.04
9	0.09
10	0.17
11	0.33
12	0.13
13	0.13
14	0.06
15	0.42
16	0.18
Subtotal:	7.06

DATE

REVISIONS

DRAWN BY

HAMILTON PARTNERS ARLINGTON HEIGHTS INDUSTRIAL

ARLINGTON HEIGHTS, ILLINOIS

EXISTING DRAINAGE EXHIBIT - PARCEL 1 / PHASE 1

975 E. 22nd St. Suite 400

Wheaton, IL 60189

630.480.7889

WWW.RWG-ENGINEERING.COM

RWG

Engineering, LLC

Civil Engineering • Real Estate Consulting • Project Management

PROJECT NO. 32227212

DATE 10/18/17

SCALE 1"=30'

PROJ. MGR. PHL

PROJ. ASSOC. RWG


DRAWN BY TMS

SHEET

1 OF 2


October 18, 2017 9:31:55 a.m. AppUser:22.Dwg (DMS Tech)

Drawing: S:\3221717 - HP ARLINGTON HEIGHTS INDUSTRIAL\300_ENGINEERING\310_CADD\DWG\322_BASE_EXISTING_DRAINAGE_EXHIBIT.DWG



EXISTING PARCEL 2 OVERFLOW
TO I-90 @ 715.02


DRAINAGE AREA SUMMARY			
Parcel 1:		Parcel 2: (cont.)	
No.	Area (ac):		
15	0.42	22	1.11
	0.18	23	0.16
17	0.34	24	0.13
18	0.07	w/ building	1.07
19	0.09	25	0.41
20	1.20	w/ building	0.45
w/ building	1.21	26	0.47
21	1.07	Subtotal:	8.36



PARCEL 2 PARCEL 1

DRAWN BY: _____
REVISIONS: _____
DATE: _____



HAMILTON PARTNERS ARLINGTON HEIGHTS INDUSTRIAL
ARLINGTON HEIGHTS, ILLINOIS
EXISTING DRAINAGE EXHIBIT - PARCEL 2 / PHASE 2

**RWG**
Engineering, LLC

975 E. 22nd St. Suite 400
Wheaton, IL 60189
630-480-7889
www.rwg-engineering.com

PROJECT NO. 3221217
DATE 10/18/17
SCALE 1"=30'
PROJ. VOR. PDS
PROJ. ASSOC. RAS
DRAWN BY 314

SHEET
2 OF 2



TOTAL NORTH PARCEL/PHASE 1 SITE:	
IMPERVIOUS	5.843 Ac.
PERVIOUS	1.197 Ac.
TOTAL	7.04 Ac.

DRAINAGE AREA	TOTAL AREA
AREA (Ac.)	(Ac.)
B6-TEMP	0.131
B7	0.524
B8	0.485
B9	0.073
B10	0.270
B11	0.261
B12	0.719
B13	0.717

DRAINAGE AREA	TOTAL AREA (Ac.)	IMPERVIOUS AREA (Ac.) "C"=0.95	PERVIOUS AREA (Ac.) "C"=0.50	COMPOSITE "C"
N1	0.096	0.056	0.040	0.76
N2	0.088	0.084	0.004	0.93
N3	0.086	0.075	0.012	0.89
N4	0.054	0.038	0.015	0.82
N5	0.119	0.113	0.006	0.93
N6	0.196	0.142	0.044	0.84
N7	0.215	0.181	0.034	0.88
N8	0.283	0.198	0.085	0.82
N9	0.093	0.056	0.036	0.77
N10	0.098	0.071	0.027	0.83
N11	0.153	0.116	0.037	0.84
N12	0.201	0.157	0.044	0.85
N13-TEMP	0.166	0.137	0.029	0.87
N14	0.210	0.198	0.012	0.92
N15	0.168	0.168	0.000	0.95
N16	0.122	0.122	0.000	0.95
N17	0.130	0.130	0.000	0.95
N18	0.121	0.121	0.000	0.95
N19	0.130	0.130	0.000	0.95
N20	0.120	0.120	0.000	0.95
N21	0.363	0.264	0.099	0.83
N22	0.230	0.000	0.230	0.50

ARLINGTON HEIGHTS INDUSTRIAL
ARLINGTON HEIGHTS, ILLINOIS
PHASE 1 (NORTH) DRAINAGE AREA EXHIBIT

975 E. 22nd St. Suite 400
Wheaton, IL 60189
630.460.7889
www.rwg-engineering.com

Engineering, LLC
Civil Engineering • Real Estate Consulting • Project Management





PROJECT NO. 3221217
DATE 09/22/17
SCALE 1"=30'
PROJ. MGR. BDL
PROJ. ASSOC. RWG
DRAWN BY. AYS

SHEET
1 OF 1

DRAINAGE AREA	TOTAL AREA (Ac.)	IMPERVIOUS AREA (Ac.) "C"=0.95	PERVIOUS AREA (Ac.) "C"=0.50	COMPOSITE "C"
N1	0.096	0.096	0.040	0.76
N2	0.088	0.088	0.004	0.93
N3	0.086	0.075	0.012	0.89
N4	0.054	0.038	0.015	0.82
N5	0.119	0.113	0.006	0.93
N6	0.186	0.142	0.044	0.84
N7	0.215	0.181	0.034	0.88
N8	0.283	0.198	0.085	0.82
N9	0.093	0.056	0.036	0.77
N10	0.098	0.071	0.027	0.83
N11	0.153	0.116	0.037	0.84
N12	0.201	0.157	0.044	0.85
N13	0.208	0.168	0.039	0.87
N14	0.210	0.198	0.012	0.92
N15	0.168	0.168	0.000	0.95
N16	0.122	0.122	0.000	0.95
N17	0.130	0.130	0.000	0.95
N18	0.121	0.121	0.000	0.95
N19	0.130	0.130	0.000	0.95
N20	0.120	0.120	0.000	0.95
N21	0.271	0.232	0.039	0.88

DRAINAGE AREA	TOTAL AREA (Ac.)	IMPERVIOUS AREA (Ac.) "C"=0.95	PERVIOUS AREA (Ac.) "C"=0.50	COMPOSITE "C"
S1	0.230	0.190	0.040	0.87
S2	0.116	0.116	0.000	0.95
S3	0.117	0.117	0.000	0.95
S4	0.134	0.134	0.000	0.95
S5	0.117	0.117	0.000	0.95
S6	0.134	0.134	0.000	0.95
S7	0.117	0.117	0.000	0.95
S8	0.134	0.134	0.000	0.95
S9	0.117	0.117	0.000	0.95
S10	0.134	0.134	0.000	0.95
S11	0.117	0.117	0.000	0.95
S12	0.134	0.134	0.000	0.95
S13	0.099	0.099	0.000	0.95
S14	0.269	0.236	0.033	0.89
S15	0.082	0.082	0.000	0.95
S16	0.178	0.153	0.025	0.89
S17	0.163	0.132	0.031	0.86
S18	0.226	0.188	0.038	0.87
S19	0.118	0.093	0.024	0.86
S20	0.150	0.114	0.037	0.84
S21	0.206	0.159	0.046	0.85
S22	0.180	0.145	0.036	0.86
S23	0.114	0.092	0.023	0.86
S24	0.140	0.105	0.035	0.84

DRAINAGE AREA	TOTAL AREA (Ac.)
B1	0.073
B2	0.269
B3	0.486
B4	0.524
B5	0.524
B6	0.262
B7	0.524
B8	0.485
B9	0.073
B10	0.270
B11	0.261
B12	0.719
B13	0.717
B14	0.718
B15	0.717
B16	0.719
B17	0.261



TOTAL SITE AREA:		
NORTH		
IMPERVIOUS	259,489 SF	(5.957 Ac.)
PERVIOUS	39,983 SF	(0.918 Ac.)
TOTAL	299,472 SF	(6.875 Ac.)
SOUTH		
IMPERVIOUS	326,595 SF	(7.498 Ac.)
PERVIOUS	45,394 SF	(1.042 Ac.)
TOTAL	371,989 SF	(8.540 Ac.)

ARLINGTON HEIGHTS INDUSTRIAL
ARLINGTON HEIGHTS, ILLINOIS
MASTER DRAINAGE AREA EXHIBIT

975 E. 22nd St., Suite 400
Wheaton, IL 60189
630-480-7889
www.rwg-engineering.com

Engineering, LLC
Civil Engineering • Real Estate Consulting • Project Management

PROJECT NO. 3221217
DATE 09/22/17
SCALE 1"=80'
PROJ. MGR. DS
PROJ. ASSOC. RNS
DRAWN BY. AIS

SHEET
1 of 1