FOR

ARLINGTON HEIGHTS - PHASE 1

2355 S. ARLINGTON HEIGHTS ROAD ARLINGTON HEIGHTS, ILLINOIS

PROJECT TEAM

Bradford Allen 300 S. Wacker Drive, 35th Floor Chicago, Illinois 60606

DEVELOPER


Moceri + Roszak 145 S. Wells Street, Suite 700 Chicago, Illinois 60606 312 423 7989


ENGINEER

V3 Companies, Ltd. 7325 Janes Avenue Woodridge, Illinois 60517 Project Manager: Steven Kranenborg, P.E skranenborg@v3co.com Project Engineer: Tom Kunschke tkunschke@v3co.com

ARCHITECT

Thomas Roszak Architecture, LLC 145 S. Wells Street, Suite 700 Chicago, Illinois 60606 773 516 3501 Contact: Paul Baulier





INDEX

CIVIL ENGINEERING PLANS

TITLE SHEET

GENERAL NOTES , LEGEND, AND ABBREVIATIONS

MWRD GENERAL NOTES AND ROUTING MAP

EXISTING CONDITIONS PLAN

DEMOLITION PLAN LAYOUT AND PAVING PLAN

GRADING PLAN

ENLARGEMENT PLANS

EROSION CONTROL PLAN

UTILITY PLAN SANITARY SEWER PROFILES

CONSTRUCTION DETAILS

CONSTRUCTION DETAILS

CONSTRUCTION DETAILS - EAST VAULT

CONSTRUCTION DETAILS - WEST VAULT

PHOTOMETRIC PLAN

SUPPORTING DOCUMENTS

ALTA/NSPS LAND TITLE AND TOPOGRAPHIC SURVEY

ALTA/NSPS LAND TITLE AND TOPOGRAPHIC SURVEY ALTA/NSPS LAND TITLE AND TOPOGRAPHIC SURVEY

4 of 4 ALTA/NSPS LAND TITLE AND TOPOGRAPHIC SURVEY

DRAINAGE STATEMENT:

TO THE BEST OF MY KNOWLEDGE AND BELIEF, THE DRAINAGE OF SURFACE WATERS WILL NOT BE CHANGED BY THE PROPOSED DEVELOPMENT. IF ANY DRAINAGE PATTERNS WILL BE CHANGED, REASONABLE PROVISIONS HAVE BEEN MADE FOR THE COLLECTION AND DIVERSION OF SUCH SURFACE WATERS INTO THE PUBLIC AREA, OR DRAINS APPROVED FOR THE USE BY THE MUNICIPAL ENGINEER, AND THAT SUCH SURFACE WATERS ARE PLANNED FOR IN ACCORDANCE WITH THE GENERALLY ACCEPTED ENGINEERING PRACTICES TO REDUCE THE LIKELIHOOD OF DAMAGES TO ADJOINING PROPERTIES.



PROFESSIONAL ENGINEER'S CERTIFICATION

CERTIFY THAT THE CIVIL ENGINEERING PLANS WERE PREPARED ON BEHALF OF THOMAS ROSZAK ARCHITECTURE, LLC BY V3 COMPANIES, LTD. UNDER MY PERSONAL DIRECTION. THI TECHNICAL SUBMISSION IS INTENDED TO BE USED AS AN INTEGRAL PART OF AND IN CONJUNCTION WITH THE PROJECT SPECIFICATIONS AND CONTRACT DOCUMENTS.

ILLINOIS LICENSED PROFESSIONAL ENGINEER

MY LICENSE EXPIRES ON NOVEMBER 30, 2023 48 hours before you dig

ILLINOIS LICENSED DESIGN FIRM NO. 184-000902

TITLE SHEET

N:\2023\230084\Drawings\ACAD\LD\S04\Sheet Drawings\C0.0 Tsht230084.dwg10/20/2023

AS NOTED

© COPYRIGHT 2023, THOMAS ROSZAK

ARCHITECTURE, LLC. DRAWINGS MAY NOT

© COPYRIGHT 2023 THOMAS ROSZAK ARCHITECTURE, LL

STEVEN KRANENBORG

Village Comments

90% CD's

80% CD's

50% CD's

ARLINGTON HEIGHTS

PHASE 1

2355 S. Arlington Heights Rd., Arlington Heights, IL 60005

Thomas Roszak Architecture, LLC

TR Management + Consulting

Thomas Roszak Architecture, LLC

4 10/20/2023 3 09/15/2023

2 07/25/2023

1 06/30/2023

Bradford Allen 300 S. Wacker Dr. 35th Floor Chicago, IL 60606 Tel: 312-994-5700

Moceri + Roszak

145 S. Wells St. Suite 700

145 S. Wells St. Suite 700

Chicago, IL 60606 Tel: 312-423-7989

Chicago, IL 60606 Tel: 312-423-7989

Chicago, IL 60606 Tel: 312-423-7989

CONSTRUCTION MANAGER SteelGrass, LLC

145 S. Wells St. Suite 700

DEVELOPMENT CONSULTANT

145 S. Wells St. Suite 700 Chicago, IL 60606 Tel: 312-423-7989 LANDSCAPE ARCHITECT

145 S. Wells St. Suite 700 Chicago, IL 60606 Tel: 312-423-7989

V3 Companies 7325 Janes Avenue Woodridge, IL 60517 Tel: 630-724-9200

STRUCTURAL ENGINEER

Chicago, IL 60611 Tel: 312-596-2000

Chicago, IL 60606 Tel: 312-201-7401 GEOTECHNICAL ENGINEER

Chicago, IL 60631 Tel: 312-985-0364

Chicago, IL 60661 Tel: 312-474-5500

MEPFP DESIGN CONSULTANT Cosentini Associates 1 S. Wacker Drive, Suite 3700

Thornton Tomasetti 330 N. Wabash Avenue, Suite 1500

8615 W. Bryn Mawr Avenue, Suite 406

GENERAL CONTRACTOR

Clark Construction Group

216 S. Jefferson Street, Suite 502

MECHANICAL DESIGN/BUILD CONTRACTOR

PLUMBING DESIGN/BUILD CONTRACTOR

ELECTRICAL DESIGN/BUILD CONTRACTOR

FIRE PROTECTION DESIGN/BUILD CONTRACTOR

EXPIRATION DATE

STATION DESIGNATION: SBM #1 ESTABLISHED BY: V3 DATE: 03-24-23 ELEVATION: 708.72 (MEASURED) DATUM: NAVD88 DESCRIPTION: SQUARE CUT ON THE SOUTH SIDE OF LIGHT BASE ON THE EAST SIDE OF S ARLINGTON HEIGHTS RD, 85'± SOUTHWESTERLY FROM THE SOUTHWEST CORNER OF BUILDING # STATION DESIGNATION: SBM #2 ESTABLISHED BY: V3 DATE: 03-24-23

DESCRIPTION: SQUARE CUT ON THE NORTH SIDE OF LIGHT BASE

ON THE SOUTH SIDE OF ALGONQUIN RD, 116'± NORTHEASTERLY

ELEVATION: 711.84 (MEASURED) DATUM: NAVD88

FROM NORTHEAST CORNER OF BUILDING # 165.

BENCHMARKS

SOURCE: BENCHMARKS ESTABLISH VIA TRIMBLE VRS NETWORK.

DATUM IS NAVD88

Contact the Metropolitan Water Reclamation District of Greater Chicago <u>2 days</u> before starting work.

P (708) 588-4055

E WMOJobStart@mwrd.org

GENERAL NOTES

1. EXISTING SITE TOPOGRAPHY, UTILITIES, RIGHT-OF-WAY AND HORIZONTAL CONTROL SHOWN ON THE DRAWINGS WERE OBTAINED FROM A SURVEY PREPARED BY:

> V3 COMPANIES, LTD. 7325 JANES AVENUE WOODRIDGE, IL 60517

COPIES OF THE SURVEY ARE AVAILABLE FROM THE SURVEYOR. SITE CONDITIONS MAY HAVE CHANGED SINCE THE SURVEY WAS PREPARED. CONTRACTORS TO VISIT SITE TO FAMILIARIZE THEMSELVES WITH THE CURRENT CONDITIONS.

- 2. ALL EXISTING TOPOGRAPHY, UNDERGROUND UTILITIES. STRUCTURES AND ASSOCIATED FACILITIES SHOWN ON THESE DRAWINGS HAVE BEEN PLOTTED FROM AVAILABLE SURVEYS AND RECORDS. THEREFORE, THEIR LOCATIONS AND ELEVATIONS MUST BE CONSIDERED APPROXIMATE ONLY. THERE MAY BE OTHER FACILITIES, THE EXISTENCE OF WHICH ARE NOT PRESENTLY KNOWN.
- 3. CONTRACTOR IS TO VERIFY ALL EXISTING STRUCTURES AND FACILITIES AND NOTIFY ENGINEER OF ANY DISCREPANCIES PRIOR TO ORDERING MATERIAL AND STARTING WORK.
- 4. ALL APPLICABLE PROVISIONS OF THE CURRENT OCCUPATIONAL SAFETY AND HEALTH ACT ARE HEREIN

INCORPORATED BY REFERENCE.

- 5. THE CONTRACTOR SHALL SUBSCRIBE TO ALL GOVERNING REGULATIONS AND SHALL OBTAIN ALL NECESSARY PUBLIC AGENCY PERMITS PRIOR TO STARTING WORK. THE CONTRACTOR, BY USING THESE PLANS FOR THEIR WORK, AGREE TO HOLD HARMLESS V3 COMPANIES LTD., THE MUNICIPALITY, THEIR EMPLOYEES AND AGENTS AND THE OWNER WHILE ACTING WITHIN THE SCOPE OF THEIR DUTIES FROM AND AGAINST ANY AND ALL LIABILITY, CLAIMS, DAMAGES, AND THE COST OF DEFENSE ARISING OUT OF CONTRACTOR(S) PERFORMANCE OF THE WORK DESCRIBED HEREIN, BUT NOT INCLUDING THE SOLE NEGLIGENCE OF THE OWNER, HIS AGENTS, THE ENGINEER, HIS EMPLOYEES AND
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL REQUIRED PERMITS FOR CONSTRUCTION ALONG OR ACROSS EXISTING STREETS OR HIGHWAYS. CONTRACTOR SHALL MAKE ARRANGEMENTS FOR THE PROPER BRACING. SHORING AND OTHER REQUIRED PROTECTION OF ALL ROADWAYS BEFORE CONSTRUCTION BEGINS. CONTRACTOR SHALL BE RESPONSIBLE FOR ANY DAMAGE TO THE STREETS OR ROADWAYS AND ASSOCIATED STRUCTURES AND SHALL MAKE REPAIRS AS NECESSARY TO THE SATISFACTION OF THE OWNER OF THE ROADWAY.
- 7. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE INSTALLATION AND MAINTENANCE OF ADEQUATE SIGNS. TRAFFIC CONTROL DEVICES AND WARNING DEVICES TO INFORM AND PROTECT THE PUBLIC DURING ALL PHASES OF CONSTRUCTION. BARRICADES AND WARNING SIGNS SHALL BE PROVIDED IN ACCORDANCE WITH THE IDOT STANDARD SPECIFICATIONS. ALL TRAFFIC CONTROL WORK SHALL BE DONE IN ACCORDANCE WITH THE "MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES."
- 8. EXCEPT WHERE MODIFIED BY THE CONTRACT DOCUMENTS, ALL WORK PROPOSED HEREON SHALL BE IN ACCORDANCE WITH THE FOLLOWING SPECIFICATIONS WHICH ARE HEREBY MADE A PART HEREOF:
- a. "STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION" AS PREPARED BY IDOT, LATEST EDITION.
- b. "STANDARD SPECIFICATIONS FOR WATER AND SEWER MAIN CONSTRUCTION IN ILLINOIS," LATEST EDITION.
- c. ILLINOIS RECOMMENDED STANDARDS FOR SEWAGE WORKS," AS PUBLISHED BY THE IEPA. LATEST EDITION.
- d. THE LATEST EDITIONS OF THE MUNICIPAL CODE AND
- STANDARDS OF THE VILLAGE OF ARLINGTON HEIGHTS.
- e. THE NATIONAL ELECTRIC CODE.
- f. THE ILLINOIS ACCESSIBILITY CODE.
- g. CLEAN CONSTRUCTION OR DEMOLITION DEBRIS (CCDD) REQUIREMENTS AS PUBLISHED BY THE IEPA. TESTING OF SOILS BEING EXPORTED FROM THE SITE AND APPROPRIATE DISPOSAL SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR. INVESTIGATION.
- IN THE EVENT OF CONFLICTING SPECIFICATIONS WITH REGARD TO SITE WORK ISSUES DESIGNED BY THE ENGINEER, THE MORE STRINGENT REQUIREMENT SHALL GOVERN.
- 9. THE CONTRACTOR SHALL NOTIFY THE AUTHORITY HAVING JURISDICTION AT LEAST 48 HOURS PRIOR TO COMMENCING ANY WORK AND FOR ANY NEW CONSTRUCTION REQUIRING INSPECTION.
- 10. ALL TREES TO BE SAVED SHALL BE IDENTIFIED PRIOR TO CONSTRUCTION AND SHALL BE PROTECTED PER IDOT STANDARDS. THE RIGHT-OF-WAY LINE AND LIMITS OF THE CONTRACTOR'S OPERATIONS SHALL BE CLEARLY DEFINED THROUGHOUT THE CONSTRUCTION PERIOD. ALL TREES IDENTIFIED TO REMAIN SHALL BE PROTECTED FROM DAMAGE INCLUDING TRUNKS, BRANCHES AND ROOTS. NO EXCAVATING, FILLING OR GRADING IS TO BE DONE INSIDE THE DRIP LINE OF TREES UNLESS OTHERWISE INDICATED. SEE LANDSCAPE PLANS FOR INFORMATION ON LANDSCAPE AND TREE PROTECTION, PRESERVATION, AND REMOVAL.
- 11. CONSTRUCTION ACCESS POINTS TO THE SITE SHALL BE PROTECTED IN SUCH A WAY AS TO PREVENT ACCUMULATION OF MUD OR SOIL ON PUBLIC THOROUGHFARES. AT THE END OF EACH DAY AND AS OFTEN AS OTHERWISE NECESSARY THE CONTRACTOR SHALL CLEAN UP ALL MUD OR SOIL WHICH HAS BEEN TRACKED ONTO PUBLIC STREETS AS REQUIRED BY THE AUTHORITIES HAVING JURISDICTION AND AS DETAILED IN THE STORM WATER POLLUTION PREVENTION PLAN.
- 12. THE CONTRACTOR SHALL PROVIDE FOR THE SAFE AND ORDERLY PASSAGE OF TRAFFIC AND PEDESTRIANS WHERE HIS/HER OPERATIONS ABUT PUBLIC THOROUGHFARES AND ADJACENT PROPERTY IN ACCORDANCE WITH THE VILLAGE OF ARLINGTON HEIGHTS MUNICIPAL CODE AND IDOT REQUIREMENTS.
- 13. NO HOLES ARE TO BE LEFT OPEN IN THE PAVEMENT OR PARKWAY OVER A HOLIDAY, WEEKEND OR AFTER 3:00 P.M. ON THE DAY PRECEDING A HOLIDAY OR A WEEKEND.
- 14. ALL EXISTING PAVEMENT OR CONCRETE TO BE REMOVED SHALL BE SAWCUT ALONG LIMITS OF PROPOSED REMOVAL BEFORE COMMENCEMENT OF PAVEMENT REMOVAL.
- 15. REMOVED PAVEMENT, SIDEWALK, CURB AND GUTTER, ETC. SHALL BE LEGALLY DISPOSED OF BY THE CONTRACTOR AS PART OF THE BASE CONTRACT.
- 16. NO BURNING OR INCINERATION OF RUBBISH WILL BE
- 17. FOR REGULATED UTILITY LOCATIONS, THE CONTRACTOR SHALL CONTACT THE JOINT UTILITY LOCATION INFORMATION FOR EXCAVATORS, "J.U.L.I.E." AT 1-800-892-0123. LOCAL GOVERNMENT AGENCIES SHOULD BE CONTACTED BY THE CONTRACTOR FOR LOCATION OF ALL NONREGULATED UTILITY LOCATIONS. CALL FOR LOCATES AT LEAST 48 HOURS IN ADVANCE OF CONSTRUCTION.
- 18. BEFORE EXCAVATING OVER OR ADJACENT TO ANY EXISTING UTILITIES, CONTRACTOR SHALL NOTIFY THE OWNER OF SUCH UTILITIES TO ENSURE THAT PROTECTIVE WORK WILL BE COORDINATED AND PERFORMED BY THE CONTRACTOR IN ACCORDANCE WITH THE REQUIREMENTS OF THE OWNER OF THE UTILITY INVOLVED. IF ANY EXISTING SERVICE LINES, UTILITIES AND UTILITY STRUCTURES WHICH ARE TO REMAIN IN SERVICE ARE UNCOVERED OR ENCOUNTERED DURING THIS OPERATION, THEY SHALL BE SAFEGUARDED, PROTECTED FROM DAMAGE AND SUPPORTED IF NECESSARY.
- 19. THE CONTRACTOR IS RESPONSIBLE FOR HAVING A SET OF "APPROVED" ENGINEERING PLANS WITH THE LATEST REVISION DATE ON THE JOB SITE PRIOR TO THE START OF CONSTRUCTION.
- 20. THE CONTRACTOR SHALL BE RESPONSIBLE FOR EROSION AND SEDIMENTATION CONTROL AS DETAILED IN THE STORM WATER POLLUTION PREVENTION PLAN.
- 21. ALL CURB RADII REFER TO BACK OF CURB.
- 22. ANY AREAS THAT ARE DISTURBED DURING CONSTRUCTION SHALL BE RESTORED IN CONFORMANCE WITH THE REQUIREMENTS OF THE AUTHORITY HAVING JURISDICTION AND SHALL BE INCIDENTAL TO THE CONTRACT.
- 23. STREET PAVING AND CURBS TO REMAIN SHALL BE PROTECTED FROM DAMAGE AND IF DAMAGED, SHALL BE REPLACED PROMPTLY IN CONFORMANCE WITH THE MUNICIPALITY OR IDOT STANDARD SPECIFICATIONS IN MATERIALS AND WORKMANSHIP.
- 24. PROPOSED ELEVATIONS INDICATE FINISHED CONDITIONS. FOR ROUGH GRADING ELEVATIONS ALLOW FOR THICKNESS OF PROPOSED PAVING (ROADS, WALKS, DRIVES, ETC.) OR TOPSOIL AS INDICATED ON DRAWINGS.

- 25. CAD FILES ARE AVAILABLE FOR CONSTRUCTION LAYOUT UPON
- 26. BACKFILL SHALL BE PLACED NEXT TO THE CURB AS SOON AS PERMISSIBLE AFTER CONSTRUCTION TO PREVENT SCOURING AND UNDERCUTTING BY STORM WATER RUNOFF.
- 27. BUTT JOINTS SHALL BE PROVIDED WHEREVER NEW PAVEMENT ABUTS EXISTING PAVEMENT. ALL BUTT JOINTS SHALL BE CONSTRUCTED BY MILLING AND SHALL BE CONSIDERED INCIDENTAL TO THE COST OF THE BITUMINOUS SURFACE
- 28. WHEN AN EXISTING DRAINAGE ROUTE, EITHER A STORM SEWER OR WATERWAY, IS INTERRUPTED DUE TO CONSTRUCTION, THE DRAINAGE ROUTE SHALL BE REESTABLISHED TO ORIGINAL CONDITIONS BY THE END OF THE SAME WORK DAY, POSITIVE DRAINAGE MUST BE MAINTAINED AT ALL TIMES DURING CONSTRUCTION.
- 29. PROVIDE SMOOTH VERTICAL CURVES THROUGH HIGH AND LOW POINTS INDICATED BY SPOT ELEVATIONS. PROVIDE UNIFORM SLOPES BETWEEN NEW AND EXISTING GRADES. AVOID RIDGES AND DEPRESSIONS.
- 30. FINAL ADJUSTMENT OF FIRE HYDRANTS, VALVE VAULTS AND MANHOLES TO FINISHED GRADE ARE INCIDENTAL TO THEIR
- 31. ANY EXISTING UTILITY STRUCTURES REQUIRING ADJUSTMENT ARE TO BE ADJUSTED OR RECONSTRUCTED BY THE CONTRACTOR TO THE UTILITY OWNER'S SATISFACTION. ADJUSTMENTS OR RECONSTRUCTIONS NOT CALLED FOR ON THE PLANS SHALL BE CONSIDERED INCIDENTAL TO THE CONTRACT.
- 32. ALL UTILITY CONNECTIONS TO EXISTING LINES SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE REGULATIONS AND TO THE SATISFACTION OF THE UTILITY OWNER.
- 33. PROVIDE TRENCH BACKFILL IN ACCORDANCE WITH THE DETAILS OF THE PLANS FOR ALL UTILITY LINES (OR AS OTHERWISE NOTED ON PLANS). BACKFILL SHALL BE PLACED AND COMPACTED PER THE MUNICIPALITY AND IDOT SPECIFICATIONS. COST OF BACKFILL IS TO BE CONSIDERED INCIDENTAL TO THE UTILITY WORK.
- 34. ANY DAMAGE TO EXISTING UTILITIES SHALL BE REPAIRED AT THE CONTRACTOR'S EXPENSE.
- 35. PRIOR TO DEMOBILIZATION, ALL WORK SHALL BE CLEANED AND INSPECTED TO THE SATISFACTION OF THE AUTHORITY HAVING JURISDICTION. THE COST OF THIS WORK SHALL BE CONSIDERED INCIDENTAL TO THE CONTRACT.
- 36. THE GENERAL CONTRACTOR SHALL COORDINATE WITH UTILITY COMPANIES TO PROVIDE CABLE TV, PHONE, ELECTRIC, GAS AND IRRIGATION SERVICES. GENERAL CONTRACTOR SHALL BE RESPONSIBLE FOR SECURING SITE LAYOUTS FOR THESE UTILITIES AND SHALL COORDINATE AND PROVIDE CONDUIT CROSSINGS AS REQUIRED. THIS COORDINATION SHALL BE CONSIDERED INCIDENTAL TO THE CONTRACT. ANY CONFLICTS IN UTILITIES SHALL BE CORRECTED BY THE GENERAL CONTRACTOR AT NO ADDITIONAL COST TO THE
- 37. BAND-SEAL CONNECTORS OR EQUIVALENT SHALL BE USED TO JOIN PIPES OF DISSIMILAR MATERIAL.
- 38. CONTRACTOR SHALL MAINTAIN ACCURATE RECORDS OF ALL CONSTRUCTION IN CONFORMANCE WITH ALL MUNICIPAL AND CLIENT REQUIREMENTS FOR USE IN PREPARING RECORD DRAWINGS.
- 39. THE SUBCONTRACTOR SHALL INSTALL A 2"x4"x6' POST ADJACENT TO THE TERMINUS OF UTILITY MAINS AND SERVICE LINES. POSTS SHALL BE MARKED IN ACCORDANCE WITH THE VILLAGE STANDARDS.
- 40. THE CONTRACTOR SHALL BE RESPONSIBLE FOR DEWATERING ANY EXCAVATION. ANY DEWATERING REQUIRED SHALL BE INCIDENTAL TO THE CONTRACT.
- 41. COPIES OF SOILS INVESTIGATION REPORTS MAY BE OBTAINED FROM THE OWNER, ANY BRACING, SHEETING OR SPECIAL CONSTRUCTION METHODS REQUIRED IN ORDER TO INSTALL THE PROPOSED IMPROVEMENTS SHALL BE CONSIDERED INCIDENTAL TO THE COST OF THE PROJECT, ANY ADDITIONAL SOILS DATA NEEDED TO CONFIRM THE CONTRACTOR'S OPINIONS OF THE SUBSOIL CONDITIONS SHALL BE DONE AT THE CONTRACTOR'S EXPENSE. THE CONTRACTOR SHALL OBTAIN THE OWNER'S WRITTEN AUTHORIZATION TO ACCESS THE SITE TO CONDUCT A SUPPLEMENTAL SOILS
- 42. ALL FIELD TILE ENCOUNTERED DURING CONSTRUCTION OPERATIONS SHALL BE CONNECTED TO THE PROPOSED STORM SEWER OR EXTENDED TO OUTLET INTO A PROPOSED DRAINAGE WAY AS DETERMINED BY THE ENGINEER. IF THIS CANNOT BE ACCOMPLISHED, THEN IT SHALL BE REPAIRED WITH NEW PIPE OF SIMILAR SIZE AND MATERIAL TO THE ORIGINAL LINE AND PUT IN ACCEPTABLE OPERATIONAL CONDITION. A RECORD OF THE LOCATION OF ALL FIELD TILE FOR ON-SITE DRAIN PIPE ENCOUNTERED SHALL BE KEPT BY THE SUBCONTRACTOR AND SUBMITTED TO THE ENGINEER UPON COMPLETION OF THE PROJECT. ALL FIELD TILE REPAIRS
- 43. THE ENGINEER AND OWNER ARE NOT RESPONSIBLE FOR THE CONSTRUCTION MEANS, METHODS, TECHNIQUES, SEQUENCES OR PROCEDURES, TIME OF PERFORMANCE, PROGRAMS OR FOR ANY SAFETY PRECAUTIONS USED BY THE CONTRACTOR. THE CONTRACTOR IS SOLELY RESPONSIBLE FOR EXECUTION OF HIS/HER WORK IN ACCORDANCE WITH THE CONTRACT DOCUMENTS AND SPECIFICATIONS.

SHALL BE CONSIDERED AS INCIDENTAL TO THE CONTRACT

AND NO ADDITIONAL COMPENSATION WILL BE PROVIDED.

SPECIFICATIONS

EARTHWORK

- 1. THE GRADING OPERATIONS ARE TO BE INSPECTED BY A THIRD PARTY SOILS ENGINEER. THE CONTRACTOR'S REPRESENTATIVE MUST BE NOTIFIED PRIOR TO ANY UNSUITABLE SOIL REMOVAL AND MUST APPROVE. IN WRITING. ANY REMEDIATION. BOTH THE CONTRACTOR AND SOILS ENGINEER MUST BE PRESENT DURING REMEDIATION.
- 2. THE PROPOSED GRADING ELEVATIONS SHOWN ON THE PLANS ARE FINISH GRADE, A MINIMUM OF 6 INCHES OF TOPSOIL IS TO BE PLACED BEFORE FINISH GRADE ELEVATIONS ARE ACHIEVED, UNLESS OTHERWISE NOTED, AREAS IN DETENTION FACILITIES NOTED TO BE ESTABLISHED WITH NATIVE VEGETATION SHALL REQUIRE A MINIMUM OF 12 INCHES OF TOPSOIL. REFER TO PLANTING PLANS TO VERIFY TOPSOIL THICKNESS REQUIREMENTS.
- 3. THE SURFACE VEGETATION, TOPSOIL, TRANSITIONAL MATERIAL, AND ANY OBVIOUSLY SOFT UNDERLYING SOIL SHALL BE STRIPPED FROM ALL AREAS TO RECEIVE STRUCTURAL FILL. IF THE UNDERLYING SUBGRADE IS FOUND TO BE UNSUITABLE FOR PROPER COMPACTION, CONTRACTOR TO CONSULT WITH SOILS ENGINEER PRIOR TO REMEDIATION.
- 4. EMBANKMENT MATERIAL WITHIN ROADWAY, DRIVEWAY, BUILDING AND OTHER STRUCTURAL CLAY FILL AREAS SHALL BE COMPACTED TO A MINIMUM OF 95% OF MAXIMUM DENSITY IN ACCORDANCE WITH ASTM SPECIFICATION D1557 (MODIFIED PROCTOR METHOD). OR TO SUCH OTHER DENSITY AS MAY BE DETERMINED APPROPRIATE BY THE SOILS ENGINEER, THE AUTHORITY HAVING JURISDICTION, AND THE CONTRACTOR.
- 5. ALL PAVEMENT SUBGRADE SHALL MEET THE REQUIREMENTS DETERMINED BY THE SOILS ENGINEER AND DOCUMENTED IN THE GEOTECHNICAL REPORT. IF AREAS OF PAVEMENT SUBGRADE ARE ENCOUNTERED WHICH DO NOT MEET THESE REQUIREMENTS, SUBGRADE REPLACEMENT OR PAVEMENT DESIGN REVISIONS SHALL BE PROVIDED WHICH ARE ADEQUATE TO OBTAIN EQUIVALENT PAVEMENT STRENGTH AS DETERMINED BY THE ENGINEER, SOILS ENGINEER, AND THE
- 6. COMPLETED GRADING (FINISHED FINE GRADE) FOR PROPOSED PAVEMENT SUBGRADE AREAS, BUILDING PADS, AND OPEN SPACE AREAS SHALL BE WITHIN A 0.1' TOLERANCE OF DESIGN SUBGRADE.

AUTHORITY HAVING JURISDICTION.

- 7. THE SUBGRADE FOR PROPOSED STREET AND PAVEMENT AREAS SHALL BE PROOF-ROLLED BY THE SUBCONTRACTOR IN THE PRESENCE OF THE JURISDICTIONAL INSPECTOR, CONTRACTOR, AND SOILS ENGINEER.
- 8. BORROW PIT LOCATION(S) SHALL BE APPROVED BY THE OWNER, ENGINEER, AND GEOTECHNICAL ENGINEER.

SANITARY SEWER

- 1. SANITARY SEWERS SHALL BE CONSTRUCTED OF THE FOLLOWING MATERIALS AS SPECIFIED ON THE PLANS:
 - A. POLYVINYL CHLORIDE PLASTIC SEWER PIPE (PVC) CONFORMING TO ASTM D2241 WITH AN SDR OF 26 WITH ELASTOMETRIC GASKET JOINTS CONFORMING TO ASTM D3139.
- B. DUCTILE IRON PIPE, CLASS 52, CONFORMING TO ANSI A21.51 (AWWA C151) WITH JOINTS CONFORMING TO ANSI 21-11 (AWWA C-111).
- 2. MANHOLES SHALL BE PRECAST CONCRETE STRUCTURES, WITH APPROPRIATE FRAME AND LIDS (SEE CONSTRUCTION DETAIL SHEETS). LIDS SHALL BE IMPRINTED "SEWER".
- 3. ALL SANITARY SEWER SHALL BE TESTED FOR LEAKAGE AND DEFLECTION IN ACCORDANCE WITH SECTION 31-1.12 AND 31-1.13 OF THE STANDARD SPECIFICATIONS FOR WATER AND SEWER MAIN
- 4. ALL SANITARY MANHOLES SHALL BE TESTED FOR WATER TIGHTNESS IN ACCORDANCE WITH ASTM C969 OR ATSM

CONSTRUCTION IN ILLINOIS.

5. CONTRACTOR SHALL VERIFY THAT THE TESTING METHODS DESIGNATED HEREIN ARE ACCEPTABLE TO LOCAL AUTHORITIES HAVING JURISDICTION OVER THIS PROJECT. IF THE LOCAL JURISDICTION HAS MORE STRINGENT TESTING REQUIREMENTS THE CONTRACTOR SHALL ADHERE TO THE MORE STRINGENT REQUIREMENTS. THE COST SHALL BE INCIDENTAL TO THE CONTRACT.

WATERMAIN DISTRIBUTION SYSTEM

1. WATER MAIN SHALL BE CONSTRUCTED OF THE FOLLOWING MATERIAL AS SPECIFIED ON THE PLANS:

> A21.51, AWWA C-151 WITH CEMENT LINING CONFORMING TO ANSI A21.4, AWWA C-104 AND PUSH-ON JOINTS CONFORMING TO ANSI A21.11, AWWA C-111. FITTINGS SHALL COMPLY WITH ANSI A21.10, AWWA C110. ALL DUCTILE IRON PIPE SHALL BE WRAPPED IN POLYETHYLENE IN ACCORDANCE WITH AWWA C105. B. POLYVINYL CHLORIDE PIPE, PVC CONFORMING TO ASTM

A. DUCTILE IRON PIPE, CLASS 52 CONFORMING TO ANSI

- C-900, WITH ELASTOMETRIC GASKET JOINTS CONFORMING TO ASTM D3139. C. WATER SERVICE LINES SHALL BE CONSTRUCTED OF
- CLASS K COPPER. 2. MINIMUM COVER OVER WATER MAIN SHALL BE 5' - 6"

FROM FINISHED GRADE TO TOP OF PIPE.

IMPRINTED "WATER".

- 3. VALVE VAULTS SHALL BE USED AT ALL VALVE LOCATIONS WHERE WATER MAIN IS 8" DIAMETER OR LARGER. VAULTS SHALL BE PRECAST CONCRETE STRUCTURES, WITH APPROPRIATE FRAME AND LIDS (SEE CONSTRUCTION DETAIL SHEETS). LIDS SHALL BE
- 4. THRUST BLOCKING OR RESTRAINED JOINTS SHALL BE INSTALLED ON WATER MAINS AT ALL BENDS, TEES, ELBOWS, ETC. AS REQUIRED BY THE AUTHORITY HAVING JURISDICTION. COST OF SAME SHALL BE INCIDENTAL TO THE UNIT PRICE FOR PIPE INSTALLED.
- 5. WATER MAIN FITTINGS (BENDS, ELBOWS, TEES, INCREASES, REDUCERS, ETC.) MAY OR MAY NOT BE SPECIFICALLY REFERENCED ON THE CONSTRUCTION PLANS. THEY ARE TO BE CONSIDERED AS INCIDENTAL AND INCLUDED IN THE LINEAL FOOTAGE COST OF THE WATER MAIN.
- 6. ALL WATER LINES ARE TO BE PRESSURE TESTED AND CHLORINATED PER THE REQUIREMENTS OF THE MUNICIPALITY AND THE ILLINOIS ENVIRONMENTAL PROTECTION AGENCY.

STORM SEWER

- 1. STORM SEWERS SHALL BE CONSTRUCTED OF THE FOLLOWING MATERIALS AS SPECIFIED ON THE PLANS:
 - A. REINFORCED CONCRETE PIPE (RCP) IN CONFORMANCE WITH IDOT STANDARD SPECIFICATIONS DETERMINATION FOR PIPE CLASS, AND CONFORMING TO ASTM C76. ALL STORM SEWER SHALL HAVE GASKETED JOINTS CONFORMING TO ASTM C-361, UNLESS OTHERWISE
 - B. POLYVINYL CHLORIDE PLASTIC SEWER PIPE (PVC) CONFORMING TO ASTM D3034 WITH FLASTOMERIC GASKETED JOINTS CONFORMING TO ASTM D3212. C. HIGH DENSITY POLYETHYLENE PIPE, HDPE, CONFORMING

TO ASTM D3350 WITH ELASTOMERIC JOINTS

CONFORMING TO ASTM D3212.

- D. DUCTILE IRON PIPE, CLASS 52, CONFORMING TO ANSI A21.51 (AWWA C151) WITH JOINTS CONFORMING TO ANSI
- 21-11 (AWWA C-111). 2. STORM SEWER STRUCTURES SHALL BE PRECAST OF THE TYPE AND DIAMETER AS SPECIFIED IN THE PLANS WITH APPROPRIATE FRAME AND LIDS (SEE CONSTRUCTION

DETAIL). LIDS SHALL BE IMPRINTED "STORM".

IEPA CROSSING REQUIREMENTS

HORIZONTAL SEPARATION:

- A. WATERMAINS SHALL BE LAID AT LEAST TEN FEET HORIZONTALLY FROM ANY EXISTING OR PROPOSED DRAIN, STORM SEWER, SANITARY SEWER OR SEWER SERVICE CONNECTION.
 - B. WATERMAINS MAY BE LAID CLOSER THAN TEN FEET TO A SEWER LINE WHEN: I. LOCAL CONDITIONS PREVENT A LATERAL SEPARATION OF TEN FEET; II. THE WATERMAIN IS AT LEAST 18 INCHES ABOVE THE CROWN OF THE SEWER; AND
 - I. BOTH THE WATERMAIN AND DRAIN OR SEWER SHALL BE CONSTRUCTED OF SLIP-ON OR MECHANICAL JOINT CAST OR DUCTILE IRON PIPE, PRESTRESSED CONCRETE PIPE, OR PVC PIPE MEETING THE REQUIREMENTS OF SECTION 653.111 WHEN IT IS IMPOSSIBLE TO MEET (A) OR (B) ABOVE. THE DRAIN OR SEWER SHALL BE PRESSURE

A. A WATERMAIN SHALL BE LAID SO THAT ITS INVERT IS 18

III. THE WATERMAIN IS EITHER IN A SEPARATE

UNDISTURBED EARTH SHELF LOCATED TO ONE

TRENCH OR IN THE SAME TRENCH ON AN

SIDE OF THE SEWER.

VERTICAL SEPARATION:

- TESTED TO THE MAXIMUM EXPECTED SURCHARGE HEAD BEFORE BACKFILLING.
- INCHES ABOVE THE CROWN OF THE DRAIN OR SEWER WHENEVER WATERMAINS CROSS STORM SEWERS, SANITARY SEWERS OR SEWER SERVICE CONNECTIONS. THE VERTICAL SEPARATION SHALL BE MAINTAINED FOR THAT PORTION OF THE WATERMAIN LOCATED WITHIN TEN FEET HORIZONTALLY OR ANY SEWER OR DRAIN CROSSED. A LENGTH OF WATERMAIN PIPE SHALL BE CENTERED OVER THE SEWER TO BE CROSSED WITH JOINTS EQUIDISTANT FROM THE SEWER OR DRAIN.
 - B. BOTH THE WATERMAIN AND SEWER SHALL BE CONSTRUCTED OF SLIP-ON OR MECHANICAL JOINT CAST OR DUCTILE IRON PIPE, PRESTRESSED CONCRETE PIPE, OR PVC PIPE MEETING REQUIREMENTS OF SECTION 653.111 WHEN:
 - I. IT IS IMPOSSIBLE TO OBTAIN THE PROPER VERTICAL SEPARATION AS DESCRIBED IN 9A) ABOVE; II. THE WATERMAIN PASSES UNDER A SEWER
 - C. A VERTICAL SEPARATION OF 18 INCHES BETWEEN THE INVERT OF THE SEWER OR DRAIN AND THE CROWN OF THE WATERMAIN SHALL BE MAINTAINED WHERE A WATERMAIN CROSSES UNDER A SEWER. SUPPORT THE SEWER OR DRAIN LINES TO PREVENT SETTLING AND BREAKING THE WATERMAIN.
 - D. CONSTRUCTION SHALL EXTEND ON EACH SIDE OF THE CROSSING UNTIL THE NORMAL DISTANCE FROM THE WATERMAIN TO THE SEWER OR DRAIN LINE IS AT LEAST TEN FEET.

PLANS FOR THICKNESS).

STANDARD SPECIFICATIONS.

- 1. BASE COURSE SHALL BE AGGREGATE BASE COURSE, CONFORMING TO IDOT STANDARD SPECIFICATIONS (SEE
- SURFACE COURSE AND BINDER COURSE SHALL BE HOT-MIX ASPHALT (HMA) CONFORMING TO IDOT STANDARD

SPECIFICATIONS (SEE PLANS FOR THICKNESS).

- CURB & GUTTER AND SIDEWALK SHALL BE CLASS SI PORTLAND CEMENT CONCRETE CONFORMING TO IDOT
- SUBGRADE SHALL BE FINISHED TO BE WITHIN 0.1 FEET OF DESIGN SUBGRADE ELEVATIONS BY THE EARTHWORK CONTRACTOR. FINE GRADING FOR PAVEMENTS AND SIDEWALKS SHALL BE THE RESPONSIBILITY OF THE PAVING
- AGGREGATE BASE COURSES SHALL BE PRIMED AT THE RATE OF 0.25 TO 0.50 GALLONS PER SQUARE YARD AND BRICK, CONCRETE, OR HMA BASES SHALL BE PRIMED AT THE RATE OF 0.05 TO 0.10 GALLONS PER SQUARE YARD WITH LIQUID ASPHALT CONFORMING TO THE IDOT STANDARD SPECIFICATIONS AND APPROPRIATE FOR PREVAILING WEATHER AND SITE CONDITIONS. PRIME COAT AND CLEANING THE EXISTING SURFACE SHALL BE CONSIDERED AS INCIDENTAL TO THE CONTRACT.
- PAVEMENT SHALL BE CONSTRUCTED ON A THOROUGHLY COMPACTED SUBGRADE MEETING THE REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND RECOMMENDATIONS OF THE GEOTECHNICAL CONSULTANT. PRIOR TO PLACEMENT OF THE NEW PAVEMENT, THE SUBGRADE SHALL BE PROOF ROLLED WITH A FULLY LOADED TANDEM AXLE DUMP TRUCK (MINIMUM 20 TONS). PROOF ROLLING SHALL BE WITNESSED BY THE GEOTECHNICAL CONSULTANT.
- SIDEWALKS SHALL BE OF THE THICKNESS AND DIMENSIONS AS SHOWN IN THE CONSTRUCTION PLANS. CONTRACTION JOINTS SHALL BE SET AT 5' CENTERS AND 1/2 INCH PREMOLDED FIBER EXPANSION JOINTS SHALL BE SET AT 50' CENTERS AND WHERE THE SIDEWALK MEETS THE CURB, A BUILDING, OR AT THE END OF EACH POUR. ALL SIDEWALKS CONSIDERED TO BE ACCESSIBLE ROUTES AS DEFINED BY THE AMERICANS WITH DISABILITIES ACT (ADA) SHALL BE SUBJECT TO ILLINOIS ACCESSIBILITY CODE (IAC) REQUIREMENTS, UNLESS OTHERWISE NOTED.
- TESTING OF THE SUBBASE, BASE COURSE, BINDER COURSE, SURFACE COURSE, AND CONCRETE WORK SHALL BE REQUIRED IN ACCORDANCE WITH IDOT STANDARD SPECIFICATIONS AND IN ACCORDANCE WITH THE SPECIFIC REQUIREMENTS OF THE AUTHORITY HAVING JURISDICTION. A QUALIFIED TESTING FIRM SHALL BE EMPLOYED TO PERFORM THE REQUIRED TESTS.
- ASPHALT JOINTS FOR BINDER AND SURFACE COURSES ARE TO BE STAGGERED.

LEGEND

EXISTING	PROPOSED	DESCRIPTION	Α
		RIGHT-OF-WAY LINE	B-B B/C
P		PROPERTY LINE (EXTERIOR)	BLDG
		LOT LINE (INTERIOR)	ВМ
		EASEMENT LINE	B/P BV/V\
X	xx	FENCE LINE	C & G
		CENTERLINE	СВ
		PROPERTY CORNER	<u>ę</u> CL
0 ——		CONTOUR	CO
		CURB & GUTTER	DIP
		DEPRESSED CURB & GUTTER	DIA
			DIWM DWG
00	× 706.0	REVERSE PITCHED CURB SPOT ELEVATION	E
.62	782.62	TOP OF CURB ELEVATION	EJ
2	782.12	EDGE OF PAVEMENT ELEVATION	ELEV E/P
		UTILITY STUB	EX.
<u> </u>	—)———)— `	SANITARY SEWER	F & C
	—»——»—	SANITARY FORCE MAIN	F & G F & O
	->>-	STORM SEWER	FES
	—— w ——	WATER MAIN	F-F
	—— G ——	GAS MAIN	FF
	T/E	UNDERGROUND TELEPHONE & ELECTRIC DUCT BANK	F/G FH
		& ELECTRIC DUCT BANK BURIED CABLE-ELECTRIC	F/L
	—— E——	BURIED CABLE-ELECTRIC BURIED CABLE-TELEPHONE	G
)———	——()——	ATLAS LOCATED UTILITY	GV/VI GV/V
•		UTILITY STRUCTURE WITH CLOSED LID	HDCF
		CURB INLET	HDPE
	<u> </u>	DRAINAGE STRUCTURE WITH OPEN LID	HDW
	~	FIRE HYDRANT	HOR HP
	▼	VALVE IN VALVE BOX	HWL
	©	GATE VALVE IN VALVE VAULT	IE IN
			LF
	-	POST INDICATOR VALVE	LP
L ₁ 1		THRUST BLOCK	L
		TREE	ME MH
		TREE LINE	MW
		CONCRETE HEADWALL	N
_)——	SUBMERGED HEADWALL	NIC
_		FLARED END SECTION (F.E.S.)	NWL OC
⊖	——————————————————————————————————————	GUY WIRES	OL
	4	FLOOD LIGHT	PC PCC
	•	UTILITY POLE	1-00
0-0	∭ □•□ •□	LIGHT STANDARD	PGL
	→>	TRAFFIC SIGNAL POLE	PI DI
		HAND HOLE	PL PP
	•	SOIL BORING	PRC
	\	IRRIGATION HEADS	PT
	•	SIGN	PUE PVC
	$_{ extstyle e$	TELEPHONE MANHOLE	. • •
	<u>(</u>	MONITORING WELL	PVI
	_ ■ τ	TELEPHONE PEDESTAL	PVT R
	 □ TP	TRANSFORMER PAD	RCP
	////	UTILITY TO BE ABANDONED	ROW
	(X) 12" XXX	FEATURE TO BE REMOVED	S SAN
	√ // ✓ / / ✓ / // ✓ /	STORMWATER FLOW DIRECTION	SAN SF
	_		SFM
		STORMWATER OVERFLOW ROUTE	SHT
	/ ⁻ \	DITCH CHECK	SHW SMH
	_/ ''	INLET FILTER BASKET	STA
		RIP RAP	ST
	0	BOLLARD	STMI T
		SILT FENCE	T/C
		WATER MAIN PROTECTION	T/P
	(C01)	UTILITY CROSSING LABEL	T/W TY
		GUARDRAIL	TYP
		RAILROAD TRACKS	UP
		RETAINING WALL	VC
		REVISION DELINEATION	VER1 VCP
	—— CLL	CONSTRUCTION LIMIT LINE	W
		CONCINCOTION LIMIT LINE	WM
		TREE PROTECTION FENCE	

BACK TO BACK OF CURB BACK OF CURB LDG BUILDING BENCHMARK BOTTOM OF PIPE BUTTERFLY VALVE IN VALVE VAULT **CURB AND GUTTER CATCH BASIN** CENTERLINE **CLOSED LID** CLEAN OUT DUCTILE IRON PIPE DIAMETER DUCTILE IRON WATER MAIN EAST OR ELECTRIC OR EDGE **EXPANSION JOINT ELEVATION** EDGE OF PAVEMENT EXISTING FRAME & CLOSED LID FRAME & GRATE FRAME & OPEN LID FLARED END SECTION FACE TO FACE OF CURB FINISHED FLOOR FINISHED GRADE FIRE HYDRANT FLOW LINE GAS LINE GATE VALVE IN VALVE BOX GATE VALVE IN VALVE VAULT DCP HANDICAP

HIGH POINT

LINEAL FEET

MATCH EXISTING

MONITORING WELL

NORMAL WATER LEVEL

POINT OF CURVATURE

PROFILE GRADE LINE

POINT OF TANGENCY

RADIUS OR RIGHT

SLOPE OR SOUTH

SILTATION FENCE

SANITARY FORCE MAIN

SUBMERGED HEADWALL

STORM STRUCTURE OR STORM SEWER

TANGENT LENGTH OR TELEPHONE

SANITARY MANHOLE

STORM MANHOLE

TOP OF CURB

TOP OF PIPE

TOP OF WALL

UTILITY POLE

VERTICAL CURVE

VITRIFIED CLAY PIPE

TYPE

TYPICAL

VERTICAL

WATER MAIN

RIGHT OF WAY

SANITARY

SHEET

STATION

PUBLIC UTILITY EASEMENT

PROPERTY LINE

POWER POLE

POINT OF INTERSECTION

NOT IN CONTRACT / NOT INCLUDED

PORTLAND CEMENT CONCRETE

OR POINT OF COMPOUND CURVE

POINT OF REVERSE CURVATURE

POINT OF VERTICAL CURVATURE

POINT OF VERTICAL INTERSECTION

OR POLYVINYL CHLORIDE PIPE

POINT OF VERTICAL TANGENCY

REINFORCED CONCRETE PIPE

MANHOLE

ON CENTER

OPEN LID

NORTH

INLET

© COPYRIGHT 2023 THOMAS ROSZAK ARCHITECTURE, LLC HIGH DENSITY POLYETHYLENE PIPE HEADWALL HORIZONTAL

#062 068598 **EXPIRATION DATE:** NOVEMBER 30, 2023 HIGH WATER LEVEL INVERT ELEVATION I CERTIFY THAT THESE DRAWINGS WERE PREPARED UNDER MY DIRECT SUPERVISION AND TO THE BEST OF MY PROFESSIONAL KNOWLEDGE THEY CONFORM TO TH VILLAGE OF ARLINGTON HEIGHTS BUILDING CODE LOW POINT OR LIGHT POLE

> 4 10/20/2023 **Village Comments** 3 09/15/2023 90% CD's 2 07/25/2023 80% CD's 1 06/30/2023 50% CD's No. Date

© COPYRIGHT 2023, THOMAS ROSZAK

ARCHITECTURE, LLC. DRAWINGS MAY NOT

STEVEN KRANENBORG

REGISTERED CIVIL ENGINEER

BE REPRODUCED WITHOUT PERMISSION

SIGNATURE/SEAL

ARLINGTON HEIGHTS PHASE ² 2355 S. Arlington Heights Rd.

Arlington Heights, IL 60005

Bradford Allen 300 S. Wacker Dr. 35th Floor Chicago, IL 60606 Tel: 312-994-5700 DEVELOPER Moceri + Roszak 145 S. Wells St. Suite 700

Chicago, IL 60606 Tel: 312-423-7989 Thomas Roszak Architecture, LLC 145 S. Wells St. Suite /00 Chicago, IL 60606 Tel: 312-423-7989

CONSTRUCTION MANAGER

SteelGrass, LLC 145 S. Wells St. Suite 700 Chicago, IL 60606 Tel: 312-423-7989 DEVELOPMENT CONSULTANT TR Management + Consulting 145 S. Wells St. Suite 700

Thomas Roszak Architecture, LLC 145 S. Wells St. Suite 700 Chicago, IL 60606 Tel: 312-423-7989 CIVIL ENGINEER V3 Companies 7325 Janes Avenue

Woodridge, IL 60517

STRUCTURAL ENGINEER

Tel: 630-724-9200

Tel: 312-423-7989

LANDSCAPE ARCHITECT

330 N. Wabash Avenue, Suite 1500 Chicago, IL 60611 Tel: 312-596-2000 MEPFP DESIGN CONSULTANT Cosentini Associates 1 S. Wacker Drive, Suite 3700 Tel: 312-201-7401 GEOTECHNICAL ENGINEER

Thornton Tomasetti

Tel: 312-985-0364 Clark Construction Group 216 S. Jefferson Street, Suite 502 Chicago, IL 60661 Tel: 312-474-5500 MECHANICAL DESIGN/BUILD CONTRACTOR

PLUMBING DESIGN/BUILD CONTRACTOR

8615 W. Bryn Mawr Avenue, Suite 406

ELECTRICAL DESIGN/BUILD CONTRACTOR

FIRE PROTECTION DESIGN/BUILD CONTRACTOR

GENERAL NOTES LEGEND AND ABBREVIATIONS

Project Issue Date N:\2023\230084\Drawings\ACAD\LD\S04\Sheet Drawings\C1.0 Gal230084.dwg10/20/2023

SHEET NUMBER SCALE AS NOTED

MWRD GENERAL NOTES

ALL CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE APPLICABLE SECTIONS OF THE FOLLOWING, EXCEPT AS MODIFIED

- HEREIN OR ON THE PLANS: STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION (LATEST EDITION), BY THE ILLINOIS DEPARTMENT OF TRANSPORTATION (IDOT SS) FOR ALL IMPROVEMENTS EXCEPT SANITARY SEWER AND WATER MAIN CONSTRUCTION;
- STANDARD SPECIFICATIONS FOR WATER AND SEWER MAIN CONSTRUCTION IN ILLINOIS, LATEST EDITION (SSWS) FOR SANITARY SEWER AND WATER MAIN CONSTRUCTION; VILLAGE OF ARLINGTON HEIGHTS MUNICIPAL CODE;

BE FOLLOWED ON THE IMPROVEMENTS INDICATED ON THE PLANS.

- THE METROPOLITAN WATER RECLAMATION DISTRICT OF GREATER CHICAGO (MWRD) WATERSHED MANAGEMENT
- ORDINANCE AND TECHNICAL GUIDANCE MANUAL; • IN CASE OF CONFLICT BETWEEN THE APPLICABLE ORDINANCES NOTED, THE MORE STRINGENT SHALL TAKE PRECEDENCE AND SHALL CONTROL ALL CONSTRUCTION.

THE MWRD LOCAL SEWER SYSTEMS SECTION FIELD OFFICE MUST BE NOTIFIED AT LEAST TWO (2) WORKING DAYS PRIOR TO THE COMMENCEMENT OF ANY WORK (CALL 708-588-4055).

- 2. THE VILLAGE OF ARLINGTON HEIGHTS ENGINEERING DEPARTMENT AND PUBLIC MUST BE NOTIFIED AT LEAST 24 HOURS PRIOR TO THE START OF CONSTRUCTION AND PRIOR TO EACH PHASE OF WORK. CONTRACTOR SHALL DETERMINE ITEMS REQUIRING INSPECTION PRIOR TO START OF CONSTRUCTION OR EACH WORK PHASE.
- 3. THE CONTRACTOR SHALL NOTIFY ALL UTILITY COMPANIES PRIOR TO BEGINNING CONSTRUCTION FOR THE EXACT LOCATIONS OF UTILITIES AND FOR THEIR PROTECTION DURING CONSTRUCTION. IF EXISTING UTILITIES ARE ENCOUNTERED THAT CONFLICT IN LOCATION WITH NEW CONSTRUCTION, IMMEDIATELY NOTIFY THE ENGINEER SO THAT THE CONFLICT CAN BE RESOLVED. CALL J.U.L.I.E. AT 1-800-892-0123.

ALL ELEVATIONS SHOWN ON PLANS REFERENCE THE NORTH AMERICAN VERTICAL DATUM OF 1988 (NAVD88). CONVERSION FACTOR IS 0 FT.

- 2. MWRD, THE MUNICIPALITY AND THE OWNER OR OWNER'S REPRESENTATIVE SHALL HAVE THE AUTHORITY TO INSPECT, APPROVE, AND REJECT THE CONSTRUCTION IMPROVEMENTS.
- 3. THE CONTRACTOR(S) SHALL INDEMNIFY THE OWNER, ENGINEER, MUNICIPALITY, MWRD, AND THEIR AGENTS, ETC., FROM ALL LIABILITY INVOLVED WITH THE CONSTRUCTION, INSTALLATION, OR TESTING OF THIS WORK ON THE PROJECT. 4. THE PROPOSED IMPROVEMENTS MUST BE CONSTRUCTED IN ACCORDANCE WITH THE ENGINEERING PLANS AS APPROVED BY MWRD AND THE MUNICIPALITY UNLESS CHANGES ARE APPROVED BY MWRD, THE MUNICIPALITY, OR AUTHORIZED AGENT. THE
- 5. THE LOCATION OF VARIOUS UNDERGROUND UTILITIES WHICH ARE SHOWN ON THE PLANS ARE FOR INFORMATION ONLY AND REPRESENT THE BEST KNOWLEDGE OF THE ENGINEER. VERIFY LOCATIONS AND ELEVATIONS PRIOR TO BEGINNING THE CONSTRUCTION OPERATIONS.

CONSTRUCTION DETAILS, AS PRESENTED ON THE PLANS, MUST BE FOLLOWED. PROPER CONSTRUCTION TECHNIQUES MUST

- 6. ANY EXISTING PAVEMENT, SIDEWALK, DRIVEWAY, ETC., DAMAGED DURING CONSTRUCTION OPERATIONS AND NOT CALLED
- FOR TO BE REMOVED SHALL BE REPLACED AT THE EXPENSE OF THE CONTRACTOR.
- 7. MATERIAL AND COMPACTION TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE REQUIREMENTS OF THE MUNICIPALITY, MWRD, AND OWNER.
- 8. THE UNDERGROUND CONTRACTOR SHALL MAKE ALL NECESSARY ARRANGEMENTS TO NOTIFY ALL INSPECTION AGENCIES. 9. ALL NEW AND EXISTING UTILITY STRUCTURES ON SITE AND IN AREAS DISTURBED DURING CONSTRUCTION SHALL BE
- ADJUSTED TO FINISH GRADE PRIOR TO FINAL INSPECTION. 10. RECORD DRAWINGS SHALL BE KEPT BY THE CONTRACTOR AND SUBMITTED TO THE ENGINEER AS SOON AS UNDERGROUND IMPROVEMENTS ARE COMPLETED. FINAL PAYMENTS TO THE CONTRACTOR SHALL BE HELD UNTIL THEY ARE RECEIVED. ANY
- CHANGES IN LENGTH, LOCATION OR ALIGNMENT SHALL BE SHOWN IN RED. ALL WYES OR BENDS SHALL BE LOCATED FROM THE DOWNSTREAM MANHOLE. ALL VALVES, B-BOXES, TEES OR BENDS SHALL BE TIED TO A FIRE HYDRANT.
- THE CONTRACTOR SHALL TAKE MEASURES TO PREVENT ANY POLLUTED WATER, SUCH AS GROUND AND SURFACE WATER, FROM ENTERING THE EXISTING SANITARY SEWERS.
- 2. A WATER-TIGHT PLUG SHALL BE INSTALLED IN THE DOWNSTREAM SEWER PIPE AT THE POINT OF SEWER CONNECTION PRIOR TO COMMENCING ANY SEWER CONSTRUCTION. THE PLUG SHALL REMAIN IN PLACE UNTIL REMOVAL IS AUTHORIZED BY THE MUNICIPALITY AND/OR MWRD AFTER THE SEWERS HAVE BEEN TESTED AND ACCEPTED.
- 3. DISCHARGING ANY UNPOLLUTED WATER INTO THE SANITARY SEWER SYSTEM FOR THE PURPOSE OF SEWER FLUSHING OF LINES FOR THE DEFLECTION TEST SHALL BE PROHIBITED WITHOUT PRIOR APPROVAL FROM THE MUNICIPALITY OR MWRD.
- 4. ALL SANITARY SEWER CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS FOR WATER AND SEWER MAIN CONSTRUCTION IN ILLINOIS (LATEST EDITION).
- 5. ALL FLOOR DRAINS SHALL DISCHARGE TO THE SANITARY SEWER SYSTEM.
- 6. ALL DOWNSPOUTS AND FOOTING DRAINS SHALL DISCHARGE TO THE STORM SEWER SYSTEM.
- 7. ALL SANITARY SEWER PIPE MATERIALS AND JOINTS (AND STORM SEWER PIPE MATERIALS AND JOINTS IN A COMBINED SEWER AREA) SHALL CONFORM TO THE FOLLOWING:
- PIPE SPECIFICATIONS JOINT SPECIFICATIONS VERIFIED CLAY PIPE ASTM C-700 ASTM C-425 ASTM C-443 REINFORCED CONCRETE SEWER PIPE ASTM C-76 ASTM C-564 CAST IRON SOIL PIPE ASTM A-74 DUCTILE IRON PIPE ANSI A21.51 ANSI A21.11 POLYVINYL CHLORIDE (PVC) PIPE ASTM D-3212 6-INCH TO 15-INCH DIAMETER SDR 26 ASTM D-3034 18-INCH TO 27-INCH DIAMETER F/DY=46 ASTM F-679 ASTM D-3212 HIGH DENSITY POLYETHYLENE (HDPE) ASTM D-3350 ASTM D-3261,F-2620 (HEAT FUSION) ASTM D-3035 ASTM D-3212,F-477 (GASKETED) WATER MAIN QUALITY PVC 4-INCH TO 36-INCH ASTM D-2241 ASTM D-2672 OR ASTM D-3139 4-INCH TO 12-INCH AWWA C900 ASTM D-3212 14-INCH TO 48-INCH AWWA C905 ASTM D-3212
- 8. ALL SANITARY SEWER CONSTRUCTION (AND STORM SEWER CONSTRUCTION IN COMBINED SEWER AREAS), REQUIRES STONE BEDDING WITH STONE ¼ " TO 1" IN SIZE, WITH MINIMUM BEDDING THICKNESS EQUAL TO ¼ THE OUTSIDE DIAMETER OF THE SEWER PIPE, BUT NOT LESS THAN FOUR (4) INCHES NOR MORE THAN EIGHT (8) INCHES. MATERIAL SHALL BE CA-11 OR CA-13 AND SHALL BE EXTENDED AT LEAST 12" ABOVE THE TOP OF THE PIPE WHEN USING PVC.
- 9. "BAND SEAL" OR SIMILAR NON-SHEAR FLEXIBLE-TYPE COUPLINGS SHALL BE USED IN THE CONNECTION OF SEWER PIPES OF DISSIMILAR MATERIALS.
- 10. BELOW THE FLOOD PROTECTION ELEVATION (FPE = BFE + 2 FEET). ALL SANITARY SEWER MANHOLES AND STRUCTURES

SHALL BE PROVIDED WITH BOLTED, WATERTIGHT COVERS. SANITARY LIDS SHALL BE CONSTRUCTED WITH A CONCEALED

- PICKHOLE AND WATERTIGHT GASKET WITH THE WORD "SANITARY" CAST INTO THE LID. 11. WHEN CONNECTING TO AN EXISTING SEWER MAIN BY MEANS OTHER THAN AN EXISTING WYE, TEE, OR AN EXISTING MANHOLE, ONE OF THE FOLLOWING METHODS SHALL BE USED: a) A CIRCULAR SAW-CUT OF SEWER MAIN BY PROPER TOOLS ("SHEWER-TAP" MACHINE OR SIMILAR)
- AND PROPER INSTALLATION OF HUBWYE SADDLE OR HUB-TEE SADDLE. b) REMOVE AN ENTIRE SECTION OF PIPE (BREAKING ONLY THE TOP OF ONE BELL) AND REPLACE WITH A WYE OR TEE BRANCH SECTION.
- c) WITH PIPE CUTTER, NEATLY AND ACCURATELY CUT OUT DESIRED LENGTH OF PIPE FOR INSERTION OF PROPER FITTING, USING "BAND SEAL" OR SIMILAR COUPLINGS TO HOLD IT FIRMLY IN PLACE.
- WHENEVER A SANITARY/COMBINED SEWER CROSSES UNDER A WATER MAIN, THE MINIMUM VERTICAL DISTANCE FROM THE TOP OF THE SEWER TO THE BOTTOM OF THE WATER MAIN SHALL BE 18 INCHES, FURTHERMORE, A MINIMUM HORIZONTAL DISTANCE OF 10 FEET BETWEEN SANITARY/COMBINED SEWERS AND WATER MAINS SHALL BE MAINTAINED UNLESS: THE SEWER IS LAID IN A SEPARATE TRENCH, KEEPING A MINIMUM 18" VERTICAL SEPARATION; OR THE SEWER IS LAID IN THE SAME TRENCH WITH THE WATER MAIN LOCATED AT THE OPPOSITE SIDE ON A BENCH OF UNDISTURBED EARTH, KEEPING A MINIMUM 18" VERTICAL SEPARATION. IF EITHER THE VERTICAL OR HORIZONTAL DISTANCES DESCRIBED ABOVE CANNOT BE MAINTAINED, OR THE SEWER CROSSES ABOVE THE WATER MAIN, THE SEWER SHALL BE CONSTRUCTED TO WATER MAIN STANDARDS.

- 13. ALL EXISTING SEPTIC SYSTEMS SHALL BE ABANDONED. ABANDONED TANKS SHALL BE FILLED WITH GRANULAR MATERIAL OR
- 14. ALL SANITARY MANHOLES, (AND STORM MANHOLES IN COMBINED SEWER AREAS), SHALL HAVE A MINIMUM INSIDE DIAMETER OF 48 INCHES, AND SHALL BE CAST IN PLACE OR PRE-CAST REINFORCED CONCRETE.
- 15. ALL SANITARY MANHOLES, (AND STORM MANHOLES IN COMBINED SEWER AREAS), SHALL HAVE PRECAST "RUBBER BOOTS" THAT CONFORM TO ASTM C-923 FOR ALL PIPE CONNECTIONS. PRECAST SECTIONS SHALL CONSIST OF MODIFIED GROOVE TONGUE AND RUBBER GASKET TYPE JOINTS.
- 16. ALL ABANDONED SANITARY SEWERS SHALL BE PLUGGED AT BOTH ENDS WITH AT LEAST 2 FEET LONG NON-SHRINK CONCRETE OR MORTAR PLUG.
- 17. EXCEPT FOR FOUNDATION/FOOTING DRAINS PROVIDED TO PROTECT BUILDINGS, OR PERFORATED PIPES ASSOCIATED WITH VOLUME CONTROL FACILITIES, DRAIN TILES/FIELD TILES/UNDERDRAINS/PERFORATED PIPES ARE NOT ALLOWED TO BE CONNECTED TO OR TRIBUTARY TO COMBINED SEWERS, SANITARY SEWERS, OR STORM SEWERS TRIBUTARY TO COMBINED SEWERS IN COMBINED SEWER AREAS. CONSTRUCTION OF NEW FACILITIES OF THIS TYPE IS PROHIBITED; AND ALL EXISTING DRAIN TILES AND PERFORATED PIPES ENCOUNTERED WITHIN THE PROJECT AREA SHALL BE PLUGGED OR REMOVED, AND SHALL NOT BE CONNECTED TO COMBINED SEWERS, SANITARY SEWERS, OR STORM SEWERS TRIBUTARY TO COMBINED
- 18. A BACKFLOW PREVENTER IS REQUIRED FOR ALL DETENTION BASINS TRIBUTARY TO COMBINED SEWERS. REQUIRED BACKFLOW PREVENTERS SHALL BE INSPECTED AND EXERCISED ANNUALLY BY THE PROPERTY OWNER TO ENSURE PROPER OPERATION, AND ANY NECESSARY MAINTENANCES SHALL BE PERFORMED TO ENSURE FUNCTIONALITY. IN THE EVENT OF A SEWER SURCHARGE INTO AN OPEN DETENTION BASIN TRIBUTARY TO COMBINED SEWERS, THE PERMITTEE SHALL ENSURE THAT CLEAN UP AND WASH OUT OF SEWAGE TAKES PLACE WITHIN 48 HOURS OF THE STORM EVENT.
- 1. THE CONTRACTOR SHALL INSTALL THE EROSION AND SEDIMENT CONTROL DEVICES AS SHOWN ON THE APPROVED EROSION AND SEDIMENT CONTROL PLAN.
- 2. EROSION AND SEDIMENT CONTROL PRACTICES SHALL BE FUNCTIONAL PRIOR TO HYDROLOGIC DISTURBANCE OF THE SITE.

3. ALL DESIGN CRITERIA, SPECIFICATIONS, AND INSTALLATION OF EROSION AND SEDIMENT CONTROL PRACTICES SHALL BE IN

4. A COPY OF THE APPROVED EROSION AND SEDIMENT CONTROL PLAN SHALL BE MAINTAINED ON THE SITE AT ALL TIMES.

ACCORDANCE WITH THE ILLINOIS URBAN MANUAL.

TEMPORARY SEDIMENT BASINS.

AREAS OR THE COMBINED SEWER SYSTEM.

INCH OF RAINFALL OR LIQUID EQUIVALENT PRECIPITATION.

- 5. INSPECTIONS AND DOCUMENTATION SHALL BE PERFORMED, AT A MINIMUM: a) UPON COMPLETION OF INITIAL EROSION AND SEDIMENT CONTROL MEASURES, PRIOR TO ANY SOIL DISTURBANCE. b) ONCE EVERY SEVEN (7) CALENDAR DAYS AND WITHIN 24 HOURS OF THE END OF A STORM EVENT WITH GREATER THAN 0.5
- 6. SOIL DISTURBANCE SHALL BE CONDUCTED IN SUCH A MANNER AS TO MINIMIZE EROSION. IF STRIPPING, CLEARING, GRADING, OR LANDSCAPING ARE TO BE DONE IN PHASES, THE CO-PERMITTEE SHALL PLAN FOR APPROPRIATE SOIL EROSION AND

ANY POINT WHERE TRAFFIC WILL BE ENTERING OR LEAVING A CONSTRUCTION SITE. SEDIMENT OR SOIL REACHING AN

8. CONCRETE WASHOUT FACILITIES SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE ILLINOIS URBAN MANUAL AND SHALL


- SEDIMENT CONTROL MEASURES. 7. A STABILIZED MAT OF CRUSHED STONE MEETING THE STANDARDS OF THE ILLINOIS URBAN MANUAL SHALL BE INSTALLED AT
- IMPROVED PUBLIC RIGHT?OF?WAY, STREET, ALLEY OR PARKING AREA SHALL BE REMOVED BY SCRAPING OR STREET CLEANING AS ACCUMULATIONS WARRANT AND TRANSPORTED TO A CONTROLLED SEDIMENT DISPOSAL AREA.

BE INSTALLED PRIOR TO ANY ON SITE CONSTRUCTION ACTIVITIES INVOLVING CONCRETE.

- 9. TEMPORARY DIVERSIONS SHALL BE CONSTRUCTED AS NECESSARY TO DIRECT ALL RUNOFF FROM HYDROLOGICALLY DISTURBED AREAS TO AN APPROPRIATE SEDIMENT TRAP OR BASIN. VOLUME CONTROL FACILITIES SHALL NOT BE USED AS
- 10. DISTURBED AREAS OF THE SITE WHERE CONSTRUCTION ACTIVITIES HAVE TEMPORARILY OR PERMANENTLY CEASED SHALL BE STABILIZED WITH TEMPORARY OR PERMANENT MEASURES WITHIN SEVEN (7) DAYS.
- 11. ALL FLOOD PROTECTION AREAS AND VOLUME CONTROL FACILITIES SHALL, AT A MINIMUM, BE PROTECTED WITH A
- DOUBLE-ROW OF SILT FENCE (OR EQUIVALENT). 12. VOLUME CONTROL FACILITIES SHALL NOT BE CONSTRUCTED UNTIL ALL OF THE CONTRIBUTING DRAINAGE AREA HAS BEEN
- 13. SOIL STOCKPILES SHALL, AT A MINIMUM, BE PROTECTED WITH PERIMETER SEDIMENT CONTROLS SOIL STOCKPILES SHALL NOT BE PLACED IN FLOOD PROTECTION AREAS OR THEIR BUFFERS.
- 14. EARTHEN EMBANKMENT SIDE SLOPES SHALL BE STABILIZED WITH APPROPRIATE EROSION CONTROL BLANKET.
- 15. STORM SEWERS THAT ARE OR WILL BE FUNCTIONING DURING CONSTRUCTION SHALL BE PROTECTED BY APPROPRIATE SEDIMENT CONTROL MEASURES.
- 16. THE CONTRACTOR SHALL EITHER REMOVE OR REPLACE ANY EXISTING DRAIN TILES AND INCORPORATE THEM INTO THE
- DRAINAGE PLAN FOR THE DEVELOPMENT. DRAIN TILES CANNOT BE TRIBUTARY TO A SANITARY OR COMBINED SEWER. 17. IF DEWATERING SERVICES ARE USED, ADJOINING PROPERTIES AND DISCHARGE LOCATIONS SHALL BE PROTECTED FROM EROSION AND SEDIMENTATION. DEWATERING SYSTEMS SHOULD BE INSPECTED DAILY DURING OPERATIONAL PERIODS. THE
- SITE INSPECTOR MUST BE PRESENT AT THE COMMENCEMENT OF DEWATERING ACTIVITIES. 18. THE CONTRCTOR SHALL BE RESPONSIBLE FOR TRENCH DEWATERING AND EXCAVATION FOR THE INSTALLATION OF SANITARY SEWERS, STORM SEWERS, WATER MAINS AS WELL AS THEIR SERVICES AND OTHER APPURTENANCES. ANY TRENCH DEWATERING WHICH CONTAINS SEDIMENT SHALL PASS THROUGH A SEDIMENT SETTLING POND OR EQUALLY EFFECTIVE SEDIMENT CONTROL DEVICE. ALTERNATIVES MAY INCLUDE DEWATERING INTO A SUMP PIT, FILTER BAG OR EXISTING

VEGETATED UPSLOPE AREA. SEDIMENT LADEN WATERS SHALL NOT BE DISCHARGE TO WATERWAYS, FLOOD PROTECTION

- 19. ALL PERMANENT EROSION CONTROL PRACTICES SHALL BE INITIATED WITHIN SEVEN (7) DAYS FOLLOWING THE COMPLETION OF SOIL DISTURBING ACTIVITIES.
- 20. ALL EROSION AND SEDIMENT CONTROL MEASURES SHALL BE MAINTAINED AND REPAIRED AS NEEDED ON A YEAR-ROUND BASIS DURING CONSTRUCTION AND ANY PERIODS OF CONSTRUCTION SHUTDOWN UNTIL PERMANENT STABILIZATION IS
- 21. ALL TEMPORARY EROSION AND SEDIMENT CONTROL MEASURES SHALL BE REMOVED WITHIN THIRTY (30) DAYS AFTER PERMANENT SITE STABILIZATION.
- 22. THE EROSION AND SEDIMENT CONTROL MEASURES SHOWN ON THE PLANS ARE THE MINIMUM REQUIREMENTS. ADDITIONAL MEASURES MAY BE REQUIRED, AS DIRECTED BY THE ENGINEER SITE INSPECTOR, OR MWRD.



MWRD ROUTING MAP

© COPYRIGHT 2023, THOMAS ROSZAK

ARCHITECTURE, LLC. DRAWINGS MAY NOT


BE REPRODUCED WITHOUT PERMISSION.

SIGNATURE/SEAL

© COPYRIGHT 2023 THOMAS ROSZAK ARCHITECTURE, LLC

STEVEN KRANENBORG REGISTERED CIVIL ENGINEER #062 068598 **EXPIRATION DATE:** NOVEMBER 30, 2023

MY DIRECT SUPERVISION AND TO THE BEST OF MY PROFESSIONAL KNOWLEDGE THEY CONFORM TO THE VILLAGE OF ARLINGTON HEIGHTS BUILDING CODE



ARLINGTON HEIGHTS PHASE ²

Arlington Heights, IL 60005

2355 S. Arlington Heights Rd.

Bradford Allen 300 S. Wacker Dr. 35th Floor Chicago, IL 60606 Tel: 312-994-5700 DEVELOPER Moceri + Roszak

145 S. Wells St. Suite 700 Chicago, IL 60606 Tel: 312-423-7989 Thomas Roszak Architecture, LLC

145 S. Wells St. Suite 700 Chicago, IL 60606 Tel: 312-423-7989 CONSTRUCTION MANAGER SteelGrass, LLC 145 S. Wells St. Suite 700 Chicago, IL 60606

TR Management + Consulting 145 S. Wells St. Suite 700 Chicago, IL 60606 Tel: 312-423-7989 LANDSCAPE ARCHITECT Thomas Roszak Architecture, LLC

145 S. Wells St. Suite 700

DEVELOPMENT CONSULTANT

Tel: 312-423-7989

Chicago, IL 60606 Tel: 312-423-7989 CIVIL ENGINEER V3 Companies 7325 Janes Avenue Woodridge, IL 60517

Tel: 630-724-9200 STRUCTURAL ENGINEER Thornton Tomasetti 330 N. Wabash Avenue, Suite 1500 Chicago, IL 60611 Tel: 312-596-2000 MEPFP DESIGN CONSULTANT

1 S. Wacker Drive, Suite 3700 Chicago, IL 60606 Tel: 312-201-7401 GEOTECHNICAL ENGINEER 8615 W. Bryn Mawr Avenue, Suite 406 Chicago, IL 60631 Tel: 312-985-0364

Cosentini Associates

Chicago, IL 60661 Tel: 312-474-5500 MECHANICAL DESIGN/BUILD CONTRACTOR

PLUMBING DESIGN/BUILD CONTRACTOR

Clark Construction Group 216 S. Jefferson Street, Suite 502


ELECTRICAL DESIGN/BUILD CONTRACTOR


FIRE PROTECTION DESIGN/BUILD CONTRACTOR


MWRD GENERAL NOTES AND **ROUTING MAP**


SHEET NUMBER


AS NOTED N:\2023\230084\Drawings\ACAD\LD\S04\Sheet Drawings\C1.0 Gal230084.dwg10/20/2023






























© COPYRIGHT 2023, THOMAS ROSZAK ARCHITECTURE, LLC. DRAWINGS MAY NOT BE REPRODUCED WITHOUT PERMISSION.

SIGNATURE/SEAL

© COPYRIGHT 2023 THOMAS ROSZAK ARCHITECTURE, LLC

ILLINOIS STEVEN KRANENBORG REGISTERED CIVIL ENGINEER #062 068598 EXPIRATION DATE: NOVEMBER 30, 2023

I CERTIFY THAT THESE DRAWINGS WERE PREPARED UNDER MY DIRECT SUPERVISION AND TO THE BEST OF MY PROFESSIONAL KNOWLEDGE THEY CONFORM TO THE VILLAGE OF ARLINGTON HEIGHTS BUILDING CODE



RLINGTON HEIGHTS
PHASE 1

2355 S. Arlington Heights Rd., Arlington Heights, IL 60005

OWNER

Bradford Allen

300 S. Wacker Dr. 35th Floor
Chicago, IL 60606
Tel: 312-994-5700

DEVELOPER

Moceri + Roszak

145 S. Wells St. Suite 700

Chicago, IL 60606
Tel: 312-423-7989

ARCHITECT

Thomas Roszak Architecture, LLC
145 S. Wells St. Suite 700
Chicago, IL 60606
Tel: 312-423-7989

CONSTRUCTION MANAGER
SteelGrass, LLC
145 S. Wells St. Suite 700
Chicago, IL 60606
Tel: 312-423-7989

Tel: 312-423-7989

DEVELOPMENT CONSULTANT

TR Management + Consulting

145 S. Wells St. Suite 700

Chicago, IL 60606

Chicago, IL 60606
Tel: 312-423-7989

LANDSCAPE ARCHITECT
Thomas Roszak Architecture, LLC

Thomas Roszak .

145 S. Wells St. Suite 700
Chicago, IL 60606
Tel: 312-423-7989

CIVIL ENGINEER

V3 Companies

7325 Janes Avenue
Woodridge, IL 60517
Tel: 630-724-9200
STRUCTURAL ENGINEER
Thornton Tomasetti

330 N. Wabash Avenue, Suite 1500

Chicago, IL 60611
Tel: 312-596-2000

MEPFP DESIGN CONSULTANT

Cosentini Associates

1 S. Wacker Drive, Suite 3700
Chicago, IL 60606
Tel: 312-201-7401

GEOTECHNICAL ENGINEER

GEI

8615 W. Bryn Mawr Avenue, Suite 406
Chicago, IL 60631
Tel: 312-985-0364

GENERAL CONTRACTOR
Clark Construction Group
216 S. Jefferson Street, Suite 502
Chicago, IL 60661
Tel: 312-474-5500

MECHANICAL DESIGN/BUILD CONTRACTOR

PLUMBING DESIGN/BUILD CONTRACTOR

ELECTRICAL DESIGN/BUILD CONTRACTOR

FIRE PROTECTION DESIGN/BUILD CONTRACTOR


SANITARY SEWER
PROFILES


AS NOTED

DATE


N:\2023\230084\Drawings\ACAD\LD\S04\Sheet Drawings\C5.0 Util230084.dwg10/20/2023

sheet number





Project Issue Date N:\2023\230084\Drawings\ACAD\LD\S04\Sheet Drawings\C6.0 Det230084.dwg10/20/2023




STEVEN KRANENBORG REGISTERED CIVIL ENGINEER #062 068598 **EXPIRATION DATE:**

Village Comments ARLINGTON HEIGHTS

CONSTRUCTION DETAILS -EAST VAULT

> SHEET NUMBER SCALE AS NOTED


N:\2023\230084\Drawings\ACAD\LD\S04\Sheet Drawings\C6.0 Det230084.dwg10/20/2023



© COPYRIGHT 2023, THOMAS ROSZAK ARCHITECTURE, LLC. DRAWINGS MAY NOT BE REPRODUCED WITHOUT PERMISSION.

STEVEN KRANENBORG REGISTERED CIVIL ENGINEER #062 068598 **EXPIRATION DATE:**

MY DIRECT SUPERVISION AND TO THE BEST OF MY VILLAGE OF ARLINGTON HEIGHTS BUILDING CODE



CONSTRUCTION DETAILS - WEST VAULT

AS NOTED

N:\2023\230084\Drawings\ACAD\LD\S04\Sheet Drawings\C6.0 Det230084.dwg10/20/2023

SHEET NUMBER

